

AC/SMARTSEAL EXTERNAL™ is a leak stop suitable for any material and does not react to temperature changes.

AC/SMART SEAL EXTERNAL™ can be easily applied by using fingers, and once applied, becomes a permanent seal.

- Effectively seals leaks up to 5mm and 825 psi
- Suitable for all materials
- Inert to all lubricants and refrigerant gases
- No flame, no mess in the permanent seal

AC/SMART SEAL EXTERNAL™ is resistant to normal flushing liquids, and is resistant to temperatures from -148 ° F to+ 520 ° F. The pressure resistance depends on the size of the loss:

- 580 psi- 5 mm leak diameter
- 725 psi- 2 mm leak diameter
- 825 psi- 1 mm leak diameter
-

AC/SMART SEAL EXTERNAL™ can be easily mixed by using two fingers. Once applied, the leak is closed. It is ideal for emergency sealing and does not disperse any residue into the system and, if necessary, it can be easily removed and once dried, the product can be sanded and refinished. AC/SMART SEAL EXTERNAL™ usage can be combined with AC/SMART SEAL™: the operator can first seal the larger leak from the outside and then complete the sealing process from the inside with AC/SMART SEAL™. The two products are not only compatible, but also synergic.



AC/SMARTSEAL EXTERNAL™
Counter Display Unit
Product # 210 Case



AC/SMARTSEAL EXTERNAL™
Individual Cartridge
Product # 210