




SPECIFICATIONS
BFQ140
 EXHAUST FANS

2100 HVI CERTIFIED 120 CFM/4.0 Sones @ 0.10" SP.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

- **Grill**
White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".
- **Blower Wheel**
One piece polymeric wheel 5¹/₈" diameter, 2³/₈" wide, with 48 fins.
- **Motor**
Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.
- **Fan Housing**
PC/ABS polymeric, dimensions 8¹/₂" x 9¹/₈" x 4³/₄".
- **Duct Collar**
Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- **Ventilating Area**
For bathrooms up to 120 sq. ft. For other rooms up to 150 sq. ft.
- **Single Pack Shipping Info**
Box Dim: 11" x 12" x 6"
UPC: 0-8316221401-0
Shipping Weight: 5¹/₄ lbs.

- **Unit Mounting**
Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to ³/₄", with a rough-in opening of 8¹/₂" x 9¹/₈".

EXPANDED PERFORMANCE													
	Static Pressure (inches of w.g.)								Sones @ .1 SP	Sones @ .25 SP	Fan Speed RPM	Power Watts	Amps
	0	0.05	0.1	0.15	0.2	0.25	0.3	0.35					
Air Flow - CFM	129	124	120	117	115	109	102	93	4.0	4.0	2625	68	0.8

PROJECT					ARCHITECT				
LOCATION					ENGINEER				
CONTRACTOR					SUBMITTED BY				DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS



U.S.: 820 Lincoln Avenue
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada: 8 Edvac Drive
 Brampton, Ontario L6S 5P2
 Tel: (905) 456-2033 • 800-250-8767
 Fax: (905) 456-1015