

MV

Product Specifications

MODULAR VARIABLE SPEED BLOWER CABINET

2, 3, 4, and 5 TONS

FEATURES

- Variable Speed modular blower
- Supports two-stage outdoor units
- Dehumidification Speed: 80% Airflow
- Efficient low continuous fan selection: 50% Airflow
- Upflow, horizontal right or left applications
- Downflow requires sub-base accessory
- Electronic fan control board
- Adjustable Blower time delay
- Accepts accessory two stage outdoor thermostats
- Matches with AC and HP cased coils (Hot water coil may be used, but doesn't match case size)
- 208/230-1-60 supply voltage
- Requires a "NO HEAT KIT" if installed without electric heat.
- Field installed electric heater packages from 5kW-25kW, single or three phase available separately

SERVICE

- Direct drive slide-out blower assembly

QUALITY

- Internally lined with ½ inch Tuf-Skin insulation
- Thermosetting powder coated steel cabinet

WARRANTY

- 5 year parts limited warranty



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



Model	Nominal Tons	Nominal CFM	Motor HP	Dimensions H x W x D in (mm)	Unit Weight lbs/kg	Ship Weight lbs/Kg
MV080014C	2	800	1/2	24 x 14-3/16 x 20-1/2 (610 x 360 x 521)	54/25	58/26
MV120017C	3	1200	1/2	24 x 17-1/2 x 20-1/2 (610 x 445 x 521)	58/26	62/28
MV160021C	4	1600	3/4	25 x 21 x 20-1/2 (635 x 533 x 521)	70/32	75/34
MV200024C	5	2000	3/4	25 x 24-1/2 x 20-1/2 (635 x 622 x 521)	73/33	79/36

UNIT SPECIFICATIONS - BLOWER COILS

Model Number		MV080014C	MV120017C	MV160021C	MV200024C
Application		Upflow / Downflow / Horizontal *			
Electrical Data**	Volt - Phase - Hz.	208 / 230 - 1 - 60			
	Minimum Circuit Ampacity	6.3	6.3	9.1	9.1
	Time Delay Fuse (Amps)	15			
	Maximum Fuse or Breaker Size	15			
Blower Data	Size	DD10 - 7	DD10 - 8	DD10 - 9	DD10 - 9
	Horsepower - Speed	1/2 - VAR	1/2 - VAR	3/4 - VAR	3/4 - VAR
	Full Load Amps	5.0	5.0	7.3	7.3
Transformer	Primary / Secondary - VA	(208-230 / 24 - VAC) 40 VA			
Weight	Unit / Shipping Lbs. (Kg.)	54/58 (25/26)	58/62 (26/28)	70/75 (32/34)	73/79 (33/36)

* Accessory subbase kit required for downflow application.

** Disregard if electric heat is added. Refer to Electric Heat table

Dimensions and Clearances – in (mm)

CLEARANCES

NO HEATERS

ALL Sides..... 0"

From Supply Duct..... 0"

Recommended Service From Front..... 20" (508mm)
(Service for blower, filter if installed)

WITH HEATERS

ALL Sides..... 0"

From First Three Feet of Supply Duct to Combustibles..... 1" (26mm)

From Duct after Three Feet 0"

Recommended Service From Front..... 20" (508mm)
(Service for blower, heaters if installed)

ALL DIMENSIONS IN (MM)

MODEL NUMBER IDENTIFICATION GUIDE

	1	2	3,4	5,6	7,8	9	10
	M	V	08	00	14	C	1
M = Cased Modular Blower							
V = Variable Speed ECM Motor - 208/230-1-60							
F = PSC Motor - 208/230-1-60							
B = PSC Motor - 115-1-60		TYPE					
08 = 800							
12 = 1200							
16 = 1600							
20 = 2000		NOMINAL MAX CFM					
00 = No Electric Heat		FACTORY INSTALLED ELECTRIC HEAT					
14 = 14.5"							
17 = 17.5"							
21 = 21"							
24 = 24.5"					CABINET WIDTH		
Sales Digit (Major Revision)							
Engineering Digit (Minor Revision)							

AIRFLOW ADJUST TABLE

MODEL #	AUX HEAT RANGE (KW/CFM)			
VIOLET Wire Selection	A	B	C	D
MV08	15kw	--	10kw	5 thru 7.5kw
MV12	--	15 thru 20kw	10kw	5 thru 7.5kw
MV16	--	25kw	--	5 thru 20kw
MV20	--	--	25kw	5 thru 20kw

OUTDOOR UNIT SIZE

MODEL #	OUTDOOR UNIT SIZE IN BTU'S			
BLUE Wire Selection	A	B	C	D
MV08	036	030	024	018
MV12	042	036	030	024
MV16	060	048	042	036
MV20	060	048	042	036

CFM RANGE

Modular Unit Size	Outdoor Unit Size	CFM Range
MV08	018	350 - 1200
	024	
	030	
	036	
MV12	024	415 - 1400
	030	
	036	
	042	
MV16	036	540 - 2000
	042	
	048	
	060	
MV20	036	540 - 2000
	042	
	048	
	060	

MV AIRFLOW DELIVERY (CFM) IN COOLING (EITHER A/C HP)

Modular Unit Size	Outdoor Unit Size	Single-Stage A/C Cooling		Two-Stage Cooling				Fan Only		
				A/C Cooling - High		A/C Cooling - Low				
		Nominal	Dehum	Nominal	Dehum	Nominal	Dehum	LOW	MED	HI
MV08**	18	525	420	--	--	--	--	350	420	525
	24	700	560	700	560	560	450	350	560	700
	30	875	700	--	--	--	--	440	700	875
	36	1050	840	1050	840	840	670	525	840	1050
MV12**	24	700	560	700	560	560	450	415	560	700
	30	875	700	--	--	--	--	440	700	875
	36	1050	840	1050	840	840	670	525	840	1050
	42	1225	980	--	--	--	--	615	980	1225
MV16**	30	1050	840	1050	840	840	670	540	840	1050
	36	1225	980	--	--	--	--	615	980	1225
	42	1400	1120	1400	1120	1120	900	700	1120	1400
	48	1750	1400	1750	1400	1400	1120	875	1400	1750
MV20**	36	1050	840	1050	840	840	670	540	840	1050
	42	1225	980	--	--	--	--	615	980	1225
	48	1400	1120	1400	1120	1120	900	700	1120	1400
	60	1750	1400	1750	1400	1400	1120	875	1400	1750

NOTES:

1. The above airflows result with the AC/HP CFM ADJUST select jumper set on NOM.
2. Airflow can be adjusted +15% or -10% by selecting Hi or Lo respectively for all modes except fan only.
3. Dry coil at 230 volts and with 10 kW heater and filter installed.
4. Airflows shown are valid for systems with total static pressure between 0.1 and 0.7 in. wc.

** Unit without electric heat installed

UNIT SPECIFICATIONS – No Heat Kit

No Heat Kit Model	Cabinet	Volts	Phase	Hertz	Supply circuit No.	H.P.	Maximum Motor Amps	MCA Branch Circuit Ampacity	Maximum Overcurrent Protection (Amps)	Recommended				
										Supply Wire 75°C copper			Ground Wire	
										No. of Wires	Wire Size	Max. Ft. Length	No. of Wires	Wire Size
EHIA00KN10*	MV08**	208	1	60	Single	1/2	5.0	6.3	15	2	14	118 (36 m)	1	14
		230												
	MV12**	208	1	60	Single	1/2	5.0	6.3	15	2	14	118 (36 m)	1	14
		230												
	MV16**	208	1	60	Single	3/4	7.3	9.1	15	2	14	82 (25 m)	1	14
		230												
	MV20**	208	1	60	Single	3/4	7.3	9.1	15	2	14	82 (25 m)	1	14
		230												

* No Heat Kit

** Unit without electric heat installed

MV AIRFLOW DELIVERY (CFM) IN HEAT PUMP HEATING MODE ONLY

Modular Unit Size	Outdoor Unit Size	Tap	Single-Stage HP Heating		Two-Stage Heating				Fan Only		
			HP Heating		HP Heating - High		HP Heating - Low				
			Comfort	Eff	Comfort	Eff	Comfort	Eff	LOW	MED	HI
MV08**	18	D	475	525	--	--	--	--	350	380	475
	24	C	630	700	630	700	505	560	350	505	630
	30	B	785	875	--	--	--	--	440	630	785
	36	A	945	1050	945	1050	755	840	525	755	945
MV12**	24	D	630	700	630	700	505	560	415	505	630
	30	C	785	875	--	--	--	--	440	630	785
	36	B	945	1050	945	1050	755	840	525	755	945
	42	A	1100	1225	--	--	--	--	615	880	1100
MV16**	30	D	945	1050	945	1050	755	840	540	755	945
	36	C	1100	1225	--	--	--	--	615	880	1100
	42	B	1260	1400	1260	1400	1010	1120	700	1010	1260
	48	A	1575	1750	1575	1750	1260	1400	875	1260	1575
MV20**	36	D	945	1050	945	1050	755	840	540	755	945
	42	C	1100	1225	--	--	--	--	615	880	1100
	48	B	1260	1400	1260	1400	1010	1120	700	1010	1260
	60	A	1575	1750	1575	1750	1260	1400	875	1260	1575

NOTES:

1. The above airflows result with the AC/HP CFM ADJUST select jumper set on NOM.
2. Airflow can be adjusted +15% or -10% by selecting Hi or Lo respectively for all modes except fan only.
3. Dry coil at 230 volts and with 10 kW heater and filter installed.
4. Airflows shown are valid for systems with total static pressure between 0.1 and 0.7 in. wc.

** Unit without electric heat installed

ELECTRIC HEATER STATIC DROP IN. W.C.

Single-Phase						
CFM	EHIA05	EHIA07	EHIA10	EHIA15	EHIA20	EHIA25
600	0.01	0.01	0.01	-- --	-- --	-- --
700	0.01	0.01	0.01	-- --	-- --	-- --
800	0.01	0.01	0.01	0.01	-- --	-- --
900	0.01	0.01	0.01	0.01	-- --	-- --
1000	0.01	0.01	0.01	0.01	0.02	-- --
1100	0.01	0.01	0.01	0.02	0.02	-- --
1200	0.01	0.01	0.01	0.02	0.02	-- --
1300	0.01	0.02	0.02	0.02	0.02	-- --
1400	0.01	0.02	0.02	0.02	0.03	0.03
1500	0.01	0.02	0.02	0.02	0.03	0.04
1600	0.01	0.02	0.02	0.03	0.03	0.04
1700	0.01	0.02	0.02	0.03	0.03	0.04
1800	0.01	0.02	0.02	0.03	0.04	0.04
1900	0.01	0.02	0.02	0.03	0.04	0.05
2000	0.01	0.02	0.02	0.03	0.04	0.05
Three-Phase						
CFM	-- --	-- --	EHIA10	EHIA15	EHIA20	EHIA25
600	-- --	-- --	0.01	-- --	-- --	-- --
700	-- --	-- --	0.01	-- --	-- --	-- --
800	-- --	-- --	0.01	0.01	-- --	-- --
900	-- --	-- --	0.01	0.01	-- --	-- --
1000	-- --	-- --	0.01	0.01	0.02	-- --
1100	-- --	-- --	0.01	0.02	0.02	-- --
1200	-- --	-- --	0.01	0.02	0.02	-- --
1300	-- --	-- --	0.02	0.02	0.02	-- --
1400	-- --	-- --	0.02	0.02	0.03	0.03
1500	-- --	-- --	0.02	0.02	0.03	0.04
1600	-- --	-- --	0.02	0.03	0.03	0.04
1700	-- --	-- --	0.02	0.03	0.03	0.04
1800	-- --	-- --	0.02	0.03	0.04	0.04
1900	-- --	-- --	0.02	0.03	0.04	0.05
2000	-- --	-- --	0.02	0.03	0.04	0.05
-- --	DO NOT OPERATE IN THIS AREA CFM / KW LIMIT EXCEEDED					

TECHNICAL DATA (MV only) Single Phase with Circuit Breaker

Heater Model	Supply Volt-	Nom. Heat-BTUH	Heat KW	kW Per Element	Supply Circuit No.	Heater kW Per Circuit	Heater AMPS.	Max Motor AMPS.	FLA Total AMPS.	MCA Min Circuit Ampacity	Maximum Overcurrent Protective Device (AMPS.)	Recommended **				
												Supply Wire 75 °C. Copper			Ground Wire	
												# of Wires	Wire Size	Max. Length (Ft)	# of Wires	Min Size
EHIA05KB10	240	16378	4.8	4.8	Single	4.8	20.0	7.3	27.3	34.1	35	2	8	108	1	10
	208	12283	3.6	3.6	Single	3.6	17.3	7.3	24.6	30.8	35	2	8	119	1	10
EHIA07KB10	240	24567	7.2	3.6	Single	7.2	30.0	7.3	37.3	46.6	50	2	8	79	1	10
	208	18425	5.4	2.7	Single	5.4	26.0	7.3	33.3	41.6	45	2	8	88	1	10
EHIA10KB10	240	32756	9.6	4.8	Single	9.6	40.0	7.3	47.3	59.1	60	2	6	99	1	10
	208	24567	7.2	3.6	Single	7.2	34.6	7.3	41.9	52.4	60	2	6	111	1	10
EHIA15KB10	240	49134	14.4	4.8	Single	14.4	60.0	7.3	67.3	84.1	90	2	4	110	1	8
					Mult. 1	9.6	40.0	7.3	47.3	59.1	60	2	6	99	1	10
					Mult. 2	4.8	20.0	0	20.0	25.0	25	2	10	95	1	10
	208	36851	10.8	3.6	Single	10.8	51.9	7.3	59.2	74.0	80	2	4	126	1	8
					Mult. 1	7.2	34.6	7.3	41.9	52.4	60	2	6	111	1	10
					Mult. 2	3.6	17.3	0	17.3	21.6	25	2	10	109	1	10
EHIA20KB10	240	65513	19.2	4.8	Single	19.2	80.0	7.3	87.3	109.1	110	2	2	135	1	6
					Mult. 1	9.6	40.0	7.3	47.3	59.1	60	2	6	99	1	10
					Mult. 2	9.6	40.0	0	40.0	50.0	50	2	8	73	1	10
	208	49134	14.4	3.6	Single	14.4	69.2	7.3	76.5	95.7	100	2	3	122	1	6
					Mult. 1	7.2	34.6	7.3	41.9	52.4	60	2	6	111	1	10
					Mult. 2	7.2	34.6	0	34.6	43.3	45	2	8	85	1	10
EHIA25KB10	240	81891	24	4.8	Single	24	100.0	7.3	107.3	134.1	150	2	1/0	175	1	6
					Mult. 1	9.6	40.0	6.0	46.0	57.5	60	2	6	102	1	10
					Mult. 2	9.6	40.0	0	40.0	50.0	50	2	8	74	1	10
	208	61418	18	3.6	Single	18	86.5	7.3	93.8	117.3	125	2	1	159	1	6
					Mult. 1	7.2	34.7	6.0	40.7	50.8	60	2	6	104	1	10
					Mult. 2	7.2	34.7	0	34.7	43.3	45	2	8	77	1	10
EHIA25KB10	208	61418	18	3.6	Mult. 3	3.6	17.3	0	17.3	21.7	25	2	12	62	1	10

TECHNICAL DATA (MV only) Single-Phase with Terminal Block

Heater Model	Supply Volt-	Nom. Heat-BTUH	Heat KW	kW Per Element	Supply Circuit No.	Heater kW Per Circuit	Heater AMPS.	Max Motor AMPS.	FLA Total AMPS.	MCA Min Circuit Ampacity	Maximum Overcurrent Protective Device (AMPS.)	Recommended **				
												Supply Wire 75 °C. Copper			Ground Wire	
												# of Wire	Wire Size	Max. Length (Ft)	# of Wires	Min Size
EHIA05KN10	240	16378	4.8	4.8	Single	4.8	20.0	7.3	27.3	34.1	35	2	8	108	1	10
	208	12283	3.6	3.6	Single	3.6	17.3	7.3	24.6	30.8	35	2	8	119	1	10
EHIA07KN10	240	24567	7.2	3.6	Single	7.2	30.0	7.3	37.3	46.6	50	2	8	79	1	10
	208	18425	5.4	2.7	Single	5.4	26.0	7.3	33.3	41.6	45	2	8	88	1	10

TECHNICAL DATA (MV only) Three-Phase with Circuit Breaker

Heater Model	Supply Volt-	Nom. Heat-BTUH	Heat KW	kW Per Element	Supply Circuit No.	Heater kW Per Circuit	Heater AMPS.	Max Motor AMPS.	FLA Total AMPS.	MCA Min Circuit Ampacity	Maximum Overcurrent Protective Device (AMPS.)	Recommended **				
												Supply Wire 75 °C. Copper			Ground Wire	
												# of Wires	Wire Size	Max. Length (Ft)	# of Wires	Min Size
EHIA10HB10	240	32756	9.6	3.2	Single	9.6	23.1	7.3	30.4	38.0	40	3	8	112	1	10
	208	24567	7.2	2.4	Single	7.2	20.0	7.3	27.3	34.1	35	3	8	125	1	10
EHIA15HB10	240	49134	14.4	4.8	Single	14.4	34.7	7.3	42.0	52.5	60	3	6	128	1	10
	208	36851	10.8	3.6	Single	10.8	30.0	7.3	37.3	46.6	50	3	8	91	1	10
EHIA20HB10	240	65513	19.2	3.2	Single	19.2	46.2	7.3	53.5	66.9	70	3	4	161	1	8
					Mult. 1	6.4	15.4	7.3	22.7	28.4	30	3	10	96	1	10
					Mult. 2	12.8	30.8	0	30.8	38.5	40	3	8	110	1	10
	208	49134	14.4	2.4	Single	14.4	40.0	7.3	47.3	59.1	60	3	6	114	1	10
					Mult. 1	4.8	13.3	7.3	20.6	25.8	30	3	10	106	1	10
					Mult. 2	9.6	26.7	0	26.7	33.3	35	3	8	127	1	10
EHIA25HB10	240	81891	24	4	Single	24	57.8	7.3	65.1	81.4	90	3	4	132	1	8
					Mult. 1	8	19.3	7.3	26.6	33.2	35	3	8	128	1	10
					Mult. 2	16	38.5	0	38.5	48.2	50	3	8	88	1	10
	208	61418	18	3	Single	18	50.0	7.3	57.3	71.7	80	3	4	150	1	8
					Mult. 1	6	16.7	7.3	24.0	30.0	30	3	10	91	1	10
					Mult. 2	12	33.3	0	33.3	41.7	45	3	8	102	1	10

Conversion: 1 foot = .3048 meters

** Must conform to local building codes and national standards

USA: National Electrical Code (NEC) ANSI/NFPA 70-2011

CANADA: Canadian Electrical Code CSA C22.1

HEAT STRIP STAGING

	Single-Stage Operation (no staging – all electric heat together)	Two-Stage Capable	Three-Stage Capable (with ODTS only)
Single-Phase	EHIA05KB / KN EHIA07KB / KN EHIA10KB / KN EHIA15KB EHIA20KB EHIA25KB	EHIA15KB EHIA20KB EHIA25KB	EHIA25KB
Three-Phase	EHIA10HB EHIA15HB EHIA20HB EHIA25HB	EHIA10HB EHIA15HB EHIA20HB EHIA25HB	EHIA20HB EHIA25HB

HEATER STAGING Single-Phase

ELECTRIC HEATER	VOLTAGE	TOTAL HEAT KW		1st STAGE KW (W1)		2nd STAGE KW (W2)	
		208V	240V	208V	240V	208V	240V
EHIA05KB10	208-240/1/60	3.6	4.8	3.6	4.8	-	-
EHIA07KB10	208-240/1/60	5.4	7.2	5.4	7.2	-	-
EHIA10KB10	208-240/1/60	7.2	9.6	7.2	9.6	-	-
EHIA15KB10	208-240/1/60	10.8	14.4	7.2	9.6	3.6	4.8
EHIA20KB10	208-240/1/60	14.4	19.2	7.2	9.6	7.2	9.6
EHIA25KB10	208-240/1/60	18	24	7.2	9.6	10.8	14.4
EHIA05KN10	208-240/1/60	3.6	4.8	3.6	4.8	-	-
EHIA07KN10	208-240/1/60	5.4	7.2	5.4	7.2	-	-
EHIA10KN10	208-240/1/60	7.2	9.6	7.2	9.6	-	-

HEATER STAGING Three-Phase

ELECTRIC HEATER	VOLTAGE	TOTAL HEAT KW		1st STAGE KW (W1)		2nd STAGE KW (W2)	
		208v	240v	208v	240v	208v	240v
EHIA10HB10	208-240/3/60	7.2	9.6	7.2	9.6	-	-
EHIA15HB10	208-240/3/60	10.8	14.4	10.8	14.4	-	-
EHIA20HB10	208-240/3/60	14.4	19.2	4.8	6.4	9.6	12.8
EHIA25HB10	208-240/3/60	18	24	6	8	12	16

ACCESSORIES

Model	Description	Used with MV Model
EHIA00KN10	No Heat Kit	08, 12, 16, 20
EHIA05KB10	5 kW 1-Phase w/C.B.	08, 12, 16, 20
EHIA05KN10	5 kW 1-Phase w/T.B.	08, 12, 16, 20
EHIA07KB10	7.5 kW 1-Phase w/C.B.	08, 12, 16, 20
EHIA07KN10	7.5 kW 1-Phase w/T.B.	08, 12, 16, 20
EHIA10KB10	10 kW 1-Phase w/C.B.	08, 12, 16, 20
EHIA10KN10	10 kW 1-Phase w/T.B.	08, 12, 16, 20
EHIA15KB10	15 kW 1-Phase w/C.B.	08, 12, 16, 20
EHIA20KB10	20 kW 1-Phase w/C.B.	12, 16, 20
EHIA25KB10	25 kW 1-Phase w/C.B.	16, 20
EHIA10HB10	10 kW 3-Phase w/C.B.	12, 16, 20
EHIA15HB10	15 kW 3-Phase w/C.B.	12, 16, 20
EHIA20HB10	20 kW 3-Phase w/C.B.	16, 20
EHIA25HB10	25 kW 3-Phase w/C.B.	16, 20

KN = 1-phase
KB = 1-phase
HB = 3-phase

T.B. = terminal block
C.B. = circuit breaker

OUTDOOR THERMOSTAT

Model	Description	Used with Heater size
AMF002OTA	2-Stage ODTS	15 kW and above

DOWNFLOW KIT

Model	Description	Used with MV Model
AMF008DFB1	Downflow kit	08
AMF012DFB1	Downflow kit	12
AMF016DFB1	Downflow kit	16
AMF020DFB1	Downflow kit	20

International Comfort Products, LLC
Lewisburg, Tennessee 37091 U.S.A.