

PGR5

UP to 16 SEER, UP to 12.5 EER PACKAGE GAS/ELECTRIC, 2 to 5 TONS
208/230 Volt, 1-phase, 60 Hz

REFRIGERATION CIRCUIT

- Environmentally balanced R-410A refrigerant
- Copper tube/aluminum fin condenser and evaporator coils
- Tin-coated copper evaporator coil standard
- Two stage scroll compressors standard on all models
- Two stage gas valve and two speed inducer motor on all models

EASY TO INSTALL AND SERVICE

- Installs easily on a rooftop or at ground level
- Easy three-panel accessibility for maintenance and installation
- Easily converts to down discharge applications
- Combination gas heating and electric cooling
- Low NOx units available

BUILT TO LAST

- Hail guard (3/8" spacing) wire grilles standard
- Induced-draft combustion and venting
- High efficiency ECM indoor blower motor on all models
- Pre-painted steel cabinet
- Direct spark ignition
- Stainless steel tubular heat exchanger standard
- Vertical condenser fan discharge
- Full perimeter steel base rails
- Crankcase heaters on select models
- High and low pressure switches provide added reliability for the compressor

LIMITED WARRANTY*

- 5 year No Hassle Replacement limited warranty
- 10 year parts limited warranty (including compressor and coils) and lifetime heat exchanger limited warranty with timely registration
- 5 year parts limited warranty and 20 year heat exchanger limited warranty if not registered within 90 days of original installation

* See warranty certificate for complete details and restrictions.



As an Energy Star® Partner, International Comfort Products, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.

UNIT PERFORMANCE DATA								
Model Number	COOLING			HEATING		Unit Dimensions Height x Width x Depth Inches (mm)	Operating Weight lbs (kg)	Price
	Net Capacity BTU/h High / Low	SEER	EER	Input BTU/h	Efficiency AFUE %			
PGR524040KGP*	23,000	15.00	12.00	40,000/26,000	81.00	44-1/8 x 48-3/16 x 32-5/8	344 (156)	
PGR524060KGP*	23,000	15.00	12.00	60,000/39,000	81.00	(1121 x 1224 x 829)	344 (156)	
PGR530040KGP*	29,000	15.00	12.00	40,000/26,000	81.00	44-1/8 x 48-3/16 x 32-5/8	351 (159)	
PGR530060KGP*	29,000	15.00	12.00	60,000/39,000	81.00	(1121 x 1224 x 829)	351 (159)	
PGR536060KGP*	35,400	16.00	12.50	60,000/39,000	81.00	44-3/4 x 48-3/16 x 44-1/8	447 (203)	
PGR536090KGP*	35,400	16.00	12.50	90,000/58,500	81.00	(1137 x 1224 x 1122)	447 (203)	
PGR542060KGP*	42,000	16.00	12.50	60,000/39,000	81.00	44-3/4 x 48-3/16 x 44-1/8	447 (203)	
PGR542090KGP*	42,000	16.00	12.50	90,000/58,500	81.00	(1137 x 1224 x 1122)	447 (203)	

continued on next page

PGR5 (continued)

UNIT PERFORMANCE DATA								
Model Number	COOLING			HEATING		Unit Dimensions Height x Width x Depth Inches (mm)	Operating Weight lbs (kg)	Price
	Net Capacity BTU/h High / Low	SEER	EER	Input BTU/h	Efficiency AFUE %			
PGR548090KGP*	47,500	16.00	12.30	90,000/58,500	81.00	50-3/4 x 48-3/16 x 44-1/8 (1289 x 1224 x 1122)	492 (223)	
PGR548115KGP*	47,500	16.00	12.30	115,000/75,000	81.00		492 (223)	
PGR548130KGP*	47,500	16.00	12.30	127,000/84,500	81.00		492 (223)	
PGR560090KGP*	57,000	16.00	12.30	90,000/58,500	81.00	52-3/4 x 48-3/16 x 44-1/8 (1340 x 1224 x 1122)	512 (232)	
PGR560115KGP*	57,000	16.00	12.30	115,000/75,000	81.00		512 (232)	
PGR560130KGP*	57,000	16.00	12.30	127,000/84,500	81.00		512 (232)	

* - 0 = Standard, 1 = Low NOx