

Production Status:

Performance

Evaporator Temp. (°F)
Condensing Temp. (°F)
Return Gas Temp. (°F)
Liquid Temp. (°F)
Capacity (Btu/hr)
Power (W):
Current (Amps):
EER (Btu/Wh):
Mass Flow (lbs/hr):
<u>Sound Data @</u>
Sound Power (dBA):
Vibration mils(peak-peak):
Record Date:

Mechanical

Displacement(in ³ /Rev):
Displacement(ft ³ /hr):
Overall Length (in):
Overall Width (in):
Overall Height (in):
Mounting Length (in):
Mounting Width (in):
Mounting Height (in):
Suction Size (in),Type:
Discharge Size (in),Type:
Initial Oil Charge (oz):
Oil Recharge (oz):
Net Weight (lbs):
Internal Free Volume (in ³):
Horse Power:
*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):
LRA Low* (Amp):
LRA-Half Winding (Amp):
MCC (Amps):
Max Operating Current(Amp):
RLA, MCC/1.4;use for contactor selection (Amp):
RLA, MCC/1.56;use for breaker & wire size selection (Amp):
RPM:
UL File No:
UL File Date:
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-448A HFO	460	3	60	Low Temp, Low Condensing
R-448A HFO	380/420	3	50	Low Temp, Low Condensing
R-449A HFO	460	3	60	Low Temp, Low Condensing
R-449A HFO	380/420	3	50	Low Temp, Low Condensing
R-134a HFC	460	3	60	High Temp
R-134a HFC	380/420	3	50	High Temp
R-404A HFC	460	3	60	Low Temp, Low Condensing
R-404A HFC	380/420	3	50	Low Temp, Low Condensing
R-507 HFC	460	3	60	Low Temp, Low Condensing
R-507 HFC	380/420	3	50	Low Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-22 HCFC	380/420	3	50	Low Temperature
R-502 CFC	460	3	60	Low Temperature
R-502 CFC	380/420	3	50	Low Temperature
R-407C HFC	460	3	60	Low Temp, Low Condensing
R-407C HFC	460	3	60	Low Temp, Low Condensing
R-407A HFC	460	3	60	Low Temp, Low Condensing
R-407A HFC	380/420	3	50	Low Temp, Low Condensing
R-407F HFC	460	3	60	Low Temp, Low Condensing
R-407F HFC	380/420	3	50	Low Temp, Low Condensing