

# 2DD3R63KE-TFD

HCFC, R-22, 60 Hz, 3 -Phase, 460 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	105
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	90
Capacity (Btu/hr)	73000	70000
Power (W):	6100	4720
Current (Amps):	9.25	7.60
EER (Btu/Wh):	11.90	14.80
Mass Flow (lbs/hr):	1070	930
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	5.9 Max
Record Date:	2007-06-08	

## Mechanical

Displacment(in <sup>3</sup> /Rev):	13.55
Displacment(ft <sup>3</sup> /hr):	823.21
Overall Length (in):	23.63
Overall Width (in):	15.37
Overall Height (in):	18.55
Mounting Length (in):	11.62
Mounting Width (in):	11.00
Mounting Height (in):	20.05 *
Suction Size (in),Type:	1 3/8 Sweat
Discharge Size (in),Type:	7/8 Sweat
Initial Oil Charge (oz):	80
Oil Recharge (oz):	72
Net Weight (lbs):	325.0
Internal Free Volume (in <sup>3</sup> ):	
Horse Power:	5.00
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

## Electrical

LRA-High*(Amp):	60.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	14.7
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	10.5
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	9.4
RPM:	
UL File No:	SA-2337
UL File Date:	1988-07-13
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

## Capacitors

## Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	460	3	60	Medium Temp, Low Condensing
R-404A HFC	380/420	3	50	Medium Temp, Low Condensing
R-507 HFC	460	3	60	Medium Temp, Low Condensing
R-507 HFC	380/420	3	50	Medium Temp, Low Condensing
R-22 HCFC	460	3	60	Medium Temp, Low Condensing
R-22 HCFC	380/420	3	50	Air Conditioning
R-22 HCFC	380/420	3	50	Medium Temp, Low Condensing
R-502 CFC	460	3	60	Medium Temperature
R-502 CFC	380/420	3	50	Medium Temperature
R-407C HFC	460	3	60	Medium Temp, Low Condensing

## Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407C HFC	460	3	60	Air Conditioning
R-407C HFC	380/420	3	50	UL High Temp
R-407A HFC	460	3	60	Medium Temp, Low Condensing
R-407A HFC	460	3	60	Air Conditioning
R-407A HFC	380/420	3	50	Medium Temp, Low Condensing
R-407A HFC	380/420	3	50	Air Conditioning
R-407A HFC	380/420	3	50	UL High Temp
R-407A HFC	460	3	60	Medium Temperature
R-407F HFC	460	3	60	Medium Temperature
R-407F HFC	380/420	3	50	Medium Temperature
R-448A HFO	380/420	3	50	Low Temp, Liquid Injected
R-448A HFO	460	3	60	Medium Temp, Low Condensing
R-449A HFO	460	3	60	Medium Temp, Low Condensing
R-449A HFO	380/420	3	50	Medium Temp, Low Condensing