

3DTHR17ME-TFC

HFC, R-407C, 60 Hz, 3 -Phase, 208/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	105
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	90
Capacity (Btu/hr)	185000	180000
Power (W):	16900	12950
Current (Amps):	51.00	41.10
EER (Btu/Wh):	10.95	13.90
Mass Flow (lbs/hr):	2690	2330
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	4.8 Max
Record Date:	2010-11-23	

Electrical

LRA-High*(Amp):	275.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	83.5
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	59.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	53.5
RPM:	
UL File No:	SA-2337
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment(in^3/Rev):	35.01
Displacment(ft^3/hr):	2127.41
Overall Length (in):	28.03
Overall Width (in):	15.06
Overall Height (in):	21.31
Mounting Length (in):	15.00
Mounting Width (in):	12.00
Mounting Height (in):	22.34 *
Suction Size (in),Type:	1 5/8 Sweat
Discharge Size (in),Type:	1 1/8 Sweat
Initial Oil Charge (oz):	125
Oil Recharge (oz):	115
Net Weight (lbs):	385.0
Internal Free Volume (in^3):	
Horse Power:	15.00
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-404A HFC	200/220	3	50	Medium Temp, Low Condensing
R-404A HFC	208/230	3	60	Medium Temp, Low Condensing
R-507 HFC	200/220	3	50	Medium Temp, Low Condensing
R-507 HFC	208/230	3	60	Medium Temp, Low Condensing
R-407C HFC	208/230	3	60	Medium Temp, Low Condensing
R-407A HFC	208/230	3	60	Air Conditioning
R-407A HFC	208/230	3	60	Medium Temp, Low Condensing