

4DA3R12ME-TSK

HFC, R-134a, 60 Hz, 3 -Phase, 460 V

High Temp



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	102000	62500
Power (W):	10000	7400
Current (Amps):	15.20	12.20
EER (Btu/Wh):	10.20	8.50
Mass Flow (lbs/hr):	1780	1000
<u>Sound Data @</u>		
Sound Power (dBA):		
Vibration mils(peak-peak):		3.7 Max
Record Date:	2010-11-10	

Mechanical

Displacment(in ³ /Rev):	39.27
Displacment(ft ³ /hr):	2386.12
Overall Length (in):	25.47
Overall Width (in):	21.25
Overall Height (in):	17.50
Mounting Length (in):	15.00
Mounting Width (in):	12.00
Mounting Height (in):	19.25 *
Suction Size (in),Type:	1 5/8 Sweat
Discharge Size (in),Type:	1 1/8 Sweat
Initial Oil Charge (oz):	135
Oil Recharge (oz):	125
Net Weight (lbs):	450.0
Internal Free Volume (in ³):	
Horse Power:	10.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	120.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	29.4
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	21.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	18.8
RPM:	
UL File No:	SA-2337
UL File Date:	1971-04-07

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	200	3	50	High Temp
R-134a HFC	208/230	3	60	High Temp
R-502 CFC	460	3	60	Low Temperature
R-502 CFC	208/230	3	60	Low Temperature
R-407C HFC	380/400	3	50	Low Temp, Low Condensing
R-407C HFC	380/400	3	50	Low Temp, Low Condensing
R-407C HFC	460	3	60	Low Temp, Low Condensing
R-407C HFC	208/230	3	60	Low Temp, Low Condensing
R-407A HFC	208/230	3	60	Low Temp, Low Condensing
R-407A HFC	200	3	50	Low Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407A HFC	200	3	50	Low Temp, Low Condensing
R-407A HFC	460	3	60	Low Temp, Low Condensing
R-407F HFC	208/230	3	60	Low Temp, Low Condensing
R-407F HFC	380/400	3	50	Low Temp, Low Condensing
R-407F HFC	200	3	50	Low Temp, Low Condensing
R-407F HFC	460	3	60	Low Temp, Low Condensing