

4DE3R18M0-TSK

HCFC, R-22, 60 Hz, 3 -Phase, 460 V

Air Conditioning



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	105
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	90
Capacity (Btu/hr)	216000	210000
Power (W):	18400	14100
Current (Amps):	27.75	22.70
EER (Btu/Wh):	11.70	14.80
Mass Flow (lbs/hr):	3160	2780
<u>Sound Data @</u>		
Sound Power (dBA):		
Vibration mils(peak-peak):		3.7 Max
Record Date:	2007-06-12	

Mechanical

Displacment(in ³ /Rev):	39.27
Displacment(ft ³ /hr):	2386.12
Overall Length (in):	25.41
Overall Width (in):	20.06
Overall Height (in):	18.03
Mounting Length (in):	15.00
Mounting Width (in):	12.00
Mounting Height (in):	19.31 *
Suction Size (in),Type:	1 5/8 Sweat
Discharge Size (in),Type:	1 3/8 Sweat
Initial Oil Charge (oz):	135
Oil Recharge (oz):	125
Net Weight (lbs):	450.0
Internal Free Volume (in ³):	
Horse Power:	15.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	154.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	46.6
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	33.3
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	29.9
RPM:	
UL File No:	SA-2337
UL File Date:	1971-04-07

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	460	3	60	Medium Temp, Low Condensing
R-22 HCFC	208/230	3	60	Air Conditioning
R-22 HCFC	208/230	3	60	Medium Temp, Low Condensing
R-22 HCFC	380/400	3	50	Air Conditioning
R-22 HCFC	380/400	3	50	Medium Temp, Low Condensing
R-22 HCFC	200	3	50	Air Conditioning
R-22 HCFC	200	3	50	Medium Temp, Low Condensing
R-502 CFC	460	3	60	Medium Temperature
R-502 CFC	208/230	3	60	Medium Temperature
R-502 CFC	380/400	3	50	Medium Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-502 CFC	200	3	50	Medium Temperature