

6DHNR35ME-TSK

HCFC, R-22, 60 Hz, 3 -Phase, 460 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	105
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	90
Capacity (Btu/hr)	387000	377000
Power (W):	35000	27100
Current (Amps):	52.70	43.15
EER (Btu/Wh):	11.10	13.90
Mass Flow (lbs/hr):	5700	5000
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	3.2 Max
Record Date:	2011-10-27	

Mechanical

Displacment(in ³ /Rev):	73.24
Displacment(ft ³ /hr):	4450.14
Overall Length (in):	30.19
Overall Width (in):	22.44
Overall Height (in):	17.97
Mounting Length (in):	15.00
Mounting Width (in):	12.00
Mounting Height (in):	19.16 *
Suction Size (in),Type:	2 1/8 Sweat
Discharge Size (in),Type:	1 5/8
Initial Oil Charge (oz):	115
Oil Recharge (oz):	105
Net Weight (lbs):	550.0
Internal Free Volume (in ³):	
Horse Power:	30.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	283.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	87.6
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	62.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	56.2
RPM:	
UL File No:	
UL File Date:	

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	460	3	60	Medium Temp, Low Condensing
R-404A HFC	460	3	60	Air Conditioning
R-404A HFC	208/230	3	60	Medium Temp, Low Condensing
R-404A HFC	208/230	3	60	Air Conditioning
R-404A HFC	200	3	50	Medium Temp, Low Condensing
R-404A HFC	380/400	3	50	Air Conditioning
R-404A HFC	200	3	50	Air Conditioning
R-507 HFC	380/400	3	50	Medium Temp, Low Condensing
R-507 HFC	460	3	60	Medium Temp, Low Condensing
R-507 HFC	460	3	60	Air Conditioning

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-507 HFC	208/230	3	60	Medium Temp, Low Condensing
R-507 HFC	208/230	3	60	Air Conditioning
R-507 HFC	380/400	3	50	Medium Temp, Low Condensing
R-507 HFC	380/400	3	50	Air Conditioning
R-507 HFC	200	3	50	Air Conditioning
R-22 HCFC	460	3	60	Medium Temp, Low Condensing
R-22 HCFC	208/230	3	60	Air Conditioning
R-22 HCFC	208/230	3	60	Medium Temp, Low Condensing
R-22 HCFC	380/400	3	50	Air Conditioning
R-22 HCFC	380/400	3	50	Medium Temp, Low Condensing
R-22 HCFC	200	3	50	Air Conditioning
R-22 HCFC	200	3	50	Medium Temp, Low Condensing
R-407C HFC	460	3	60	Air Conditioning
R-407C HFC	460	3	60	Medium Temp, Low Condensing
R-407C HFC	208/230	3	60	Air Conditioning
R-407C HFC	208/230	3	60	Medium Temp, Low Condensing
R-407C HFC	200	3	50	Air Conditioning
R-407C HFC	380/400	3	50	Medium Temp, Low Condensing
R-407C HFC	200	3	50	Air Conditioning
R-407C HFC	380/400	3	50	Medium Temp, Low Condensing
R-407A HFC	460	3	60	Air Conditioning
R-407A HFC	460	3	60	Medium Temp, Low Condensing
R-407A HFC	208/230	3	60	Air Conditioning
R-407A HFC	208/230	3	60	Medium Temp, Low Condensing
R-407A HFC	200	3	50	Air Conditioning
R-407A HFC	380/400	3	50	Medium Temp, Low Condensing
R-407A HFC	200	3	50	Air Conditioning
R-407A HFC	200	3	50	Medium Temp, Low Condensing
R-407F HFC	460	3	60	Medium Temp, Low Condensing
R-407F HFC	208/230	3	60	Air Conditioning
R-407F HFC	208/230	3	60	Medium Temp, Low Condensing
R-407F HFC	460	3	60	Air Conditioning
R-407F HFC	380/400	3	50	Medium Temp, Low Condensing
R-407F HFC	380/400	3	50	Air Conditioning
R-407F HFC	200	3	50	Medium Temp, Low Condensing
R-407F HFC	380/400	3	50	Air Conditioning
R-448A HFO	460	3	60	Medium Temp, Low Condensing
R-448A HFO	208/230	3	60	Medium Temp, Low Condensing
R-448A HFO	380/400	3	50	Medium Temp, Low Condensing
R-448A HFO	200	3	50	Medium Temp, Low Condensing
R-449A HFO	460	3	60	Medium Temp, Low Condensing
R-449A HFO	208/230	3	60	Medium Temp, Low Condensing
R-449A HFO	200	3	50	Medium Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-449A HFO	380/400	3	50	Medium Temp, Low Condensing