

# ARE37C3E-IAV

HFC, R-134a, 60 Hz, 1 -Phase, 208/230 V  
High Temp



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	3790	2200
Power (W):	594	429
Current (Amps):	3.40	2.90
EER (Btu/Wh):	6.40	5.10
Mass Flow (lbs/hr):	66	35
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	1999-07-08	

## Mechanical

Displacment(in <sup>3</sup> /Rev):	0.74
Displacment(ft <sup>3</sup> /hr):	89.90
Overall Length (in):	10.50
Overall Width (in):	6.40
Overall Height (in):	7.40
Mounting Length (in):	6.50
Mounting Width (in):	4.00
Mounting Height (in):	7.80 *
Suction Size (in),Type:	5/16 Stub
Discharge Size (in),Type:	1/4 Stub
Initial Oil Charge (oz):	12
Oil Recharge (oz):	10
Net Weight (lbs):	26.0
Internal Free Volume (in <sup>3</sup> ):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

## Electrical

LRA-High*(Amp):	17.3
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	4.76
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	3.4
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	3.1
RPM:	
UL File No:	SA-2337
UL File Date:	1999-03-03
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

## Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0053-30	88.0	108.0	330	

## Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
-------------	---------	-------	-----------	-------------