

ERFA-031E-TAC

HCFC, R-22, 60 Hz, 3 -Phase, 208/230 V
High Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	35200	21800
Power (W):	3840	3020
Current (Amps):	11.60	9.50
EER (Btu/Wh):	9.20	7.20
Mass Flow (lbs/hr):	555	320
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2006-12-22	

Mechanical

Displacment(in ³ /Rev):	7.59
Displacment(ft ³ /hr):	461.38
Overall Length (in):	17.69
Overall Width (in):	12.00
Overall Height (in):	12.91
Mounting Length (in):	10.06
Mounting Width (in):	10.50
Mounting Height (in):	13.94 *
Suction Size (in),Type:	1 1/8 Sweat
Discharge Size (in),Type:	5/8 Flare
Initial Oil Charge (oz):	60
Oil Recharge (oz):	55
Net Weight (lbs):	178.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	82.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	17.4
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	12.4
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	11.2
RPM:	
UL File No:	SA-2337
UL File Date:	1984-09-10
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-404A HFC	200/220	3	50	Medium Temperature
R-404A HFC	208/230	3	60	Medium Temperature
R-22 HCFC	200/220	3	50	High Temp
R-502 CFC	200/220	3	50	Medium Temperature
R-448A HFO	200/220	3	50	Medium Temperature
R-448A HFO	208/230	3	60	Medium Temperature
R-449A HFO	200/220	3	50	Medium Temperature
R-449A HFO	208/230	3	60	Medium Temperature