

FPAK-010Z-TFC-072

HFC, R-134a, 60Hz, 3- Phase, 208/230 V



Availability : Standard US Wholesaler

Mechanical

Unit Height (in):	16.6
Unit Length (in):	24.0
Unit Width (in):	17.1
Ship Weight (lbs):	100.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.375 SWEAT
Suction Connection Size (in)/Type:	0.625 SWEAT
Discharge Line Size(in):	0.375
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	11.2
Compressor:	ZS09KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	55.4
Compressor LRA - Half winding:	
Compressor RLA:	8.0
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	26-Jul-2013	Return Gas Temp. (°F):	65
Compressor:	ZS09KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	8899	Air Flow Rate (CFM)	650

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
25	7,100	117.0	27.0	7.2
30	7,810	119.2	29.2	7.7
35	8,570	121.5	31.5	8.1
40	9,370	124.0	34.0	8.5
45	10,200	126.5	36.5	8.9