

KAJA-011A-TAD

CFC, R-502, 60 Hz, 3 -Phase, 460 V

Low Temperature



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	-25	-40
Condensing Temp. (°F)	105	105
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	105	105
Capacity (Btu/hr)	3790	2150
Power (W):	801	612
Current (Amps):	1.30	1.10
EER (Btu/Wh):	4.70	3.50
Mass Flow (lbs/hr):	75	42
Sound Data @		
Sound Power (dBA):		
Vibration mils(peak-peak):		4.8 Max
Record Date:	2007-01-18	

Mechanical

Displacement(in ³ /Rev):	3.60
Displacement(ft ³ /hr):	218.71
Overall Length (in):	14.38
Overall Width (in):	9.50
Overall Height (in):	10.44
Mounting Length (in):	8.19
Mounting Width (in):	6.38
Mounting Height (in):	11.19 *
Suction Size (in),Type:	5/8 Flare
Discharge Size (in),Type:	1/2 Flare
Initial Oil Charge (oz):	22
Oil Recharge (oz):	20
Net Weight (lbs):	84.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	15.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	2.8
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	2.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	1.8
RPM:	
UL File No:	
UL File Date:	1984-07-23
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	460	3	60	UL Low Temp
R-502 CFC	380/400	3	50	Low Temperature