

M7JH-0018-IAA-078

HFC, R-134a, 60Hz, 1- Phase, 115 V



Availability : Standard US OEM

Mechanical

Unit Height (in):	11.4
Unit Length (in):	14.1
Unit Width (in):	12.1
Ship Weight (lbs):	42.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.25 SWEAT
Suction Connection Size (in)/Type:	0.375 SWEAT
Discharge Line Size(in):	0.25
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	12

Electrical

Max Fuse Size:	15
Min Circuit Ampacity:	6.8
Compressor:	ARE25C4E-IAA-103
Compressor LRA - Low:	
Compressor LRA - High:	28.5
Compressor LRA - Half winding:	
Compressor RLA:	4.9
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	0.36
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	11-May-2017	Return Gas Temp. (°F):	65
Compressor:	ARE25C4E-IAA-103 x 1	Subcooling (°F):	5
Performance No:	11492	Air Flow Rate (CFM)	223

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
0	1,020	106.7	16.7	4.2
5	1,160	108.4	18.4	4.5
10	1,310	110.3	20.3	4.8
15	1,470	112.2	22.2	5.1
20	1,640	114.3	24.3	5.4
25	1,820	116.6	26.6	5.7
30	2,020	118.9	28.9	6.1
35	2,230	121.5	31.5	6.4
40	2,450	124.1	34.1	6.7
45	2,690	126.9	36.9	6.9