

MRA2-050A-TFC

CFC, R-502, 60 Hz, 3 -Phase, 208/230 V
UL Low Temp



Production Status:

Performance

Evaporator Temp. (°F)	-25	-40
Condensing Temp. (°F)	105	105
Return Gas Temp. (°F)		
Liquid Temp. (°F)		
Capacity (Btu/hr)	19000	11520
Power (W):	4040	3010
Current (Amps):		
EER (Btu/Wh):	4.70	3.83
Mass Flow (lbs/hr):		
Sound Data @		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:		

Mechanical

Displacment(in ³ /Rev):	17.80
Displacment(ft ³ /hr):	1081.51
Overall Length (in):	22.44
Overall Width (in):	13.00
Overall Height (in):	16.94
Mounting Length (in):	11.63
Mounting Width (in):	11.00
Mounting Height (in):	18.00 *
Suction Size (in),Type:	1 3/8 Sweat
Discharge Size (in),Type:	7/8 Sweat
Initial Oil Charge (oz):	80
Oil Recharge (oz):	70
Net Weight (lbs):	290.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	115.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	30.8
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	22.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	19.7
RPM:	
UL File No:	SA-2337
UL File Date:	1972-04-26
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-12 CFC	200/220	3	50	Medium Temperature
R-12 CFC	208/230	3	60	Medium Temperature
R-502 CFC	200/220	3	50	Low Temperature