

NRM1-050A-TFD

HCFC, R-22, 50 Hz, 3 -Phase, 380/400 V
Medium Temperature



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	20	0
Condensing Temp. (°F)	120	110
Return Gas Temp. (°F)	65	50
Liquid Temp. (°F)	120	95
Capacity (Btu/hr)	36200	23800
Power (W):	5050	3900
Current (Amps):	10.90	9.00
EER (Btu/Wh):	7.20	6.10
Mass Flow (lbs/hr):	530	328
Sound Data @		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2007-01-04	

Mechanical

Displacement(in ³ /Rev):	15.98
Displacement(ft ³ /hr):	804.52
Overall Length (in):	21.06
Overall Width (in):	13.00
Overall Height (in):	15.19
Mounting Length (in):	11.63
Mounting Width (in):	11.00
Mounting Height (in):	16.22 *
Suction Size (in),Type:	1 1/8 Sweat
Discharge Size (in),Type:	5/8 Flare
Initial Oil Charge (oz):	70
Oil Recharge (oz):	65
Net Weight (lbs):	219.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical

LRA-High*(Amp):	62.5
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	15.4
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	11.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	9.9
RPM:	
UL File No:	SA-2337
UL File Date:	1972-04-26
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	460	3	60	UL Medium Temp
R-502 CFC	460	3	60	UL Medium Temp
R-502 CFC	380/400	3	50	Medium Temperature