

RST64C1-CFA

HCFC, R-22, 60 Hz, 1 -Phase, 115 V

Medium Temperature



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	20	0
Condensing Temp. (°F)	120	110
Return Gas Temp. (°F)	40	40
Liquid Temp. (°F)	120	110
Capacity (Btu/hr)	6440	4100
Power (W):	1190	902
Current (Amps):	23.40	18.00
EER (Btu/Wh):	5.40	4.55
Mass Flow (lbs/hr):	100	60
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2011-11-04	

Electrical

LRA-High*(Amp):	77.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	20.5
Max Operating Current(Amp):	
RLA, MCC/1.4;use for contactor selection (Amp):	14.6
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	13.1
RPM:	
UL File No:	
UL File Date:	
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment(in ³ /Rev):	1.37
Displacment(ft ³ /hr):	166.14
Overall Length (in):	10.30
Overall Width (in):	7.10
Overall Height (in):	9.20
Mounting Length (in):	8.00
Mounting Width (in):	4.80
Mounting Height (in):	9.90 *
Suction Size (in),Type:	1 Rotalo
Discharge Size (in),Type:	1/4 Stub
Initial Oil Charge (oz):	15
Oil Recharge (oz):	13
Net Weight (lbs):	39.0
Internal Free Volume (in ³):	
Horse Power:	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-34	243.0	292.0	250	
Run Capacitor	014-0064-14	40.0	0.0	440	

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-22 HCFC	115	1	60	High Temp