

XFAM-017Z-TFC-081

HCFC, R-22, 60Hz, 3- Phase, 208/230 V



Availability : Custom US OEM Or Wholesaler

Mechanical

Unit Height (in):	33.1
Unit Length (in):	40.6
Unit Width (in):	17.2
Ship Weight (lbs):	226.0
Condensor Type:	Air
CopeVap Water Storage:	NA
Liquid Connection Size (in)/Type:	0.5 SWEAT
Suction Connection Size (in)/Type:	0.875 SWEAT
Discharge Line Size(in):	0.5
Water Inlet (in):	
Water Outlet (in):	
Oil Type:	POE
Oil Recharge Amount (oz):	25

Electrical

Max Fuse Size:	20
Min Circuit Ampacity:	14.1
Compressor:	ZS11KAE-TF5-118
Compressor LRA - Low:	
Compressor LRA - High:	58.0
Compressor LRA - Half winding:	
Compressor RLA:	10.4
UL:	Listed
UL File #:	SA633
UL Guide Card:	LZFE
Amps Per Motor:	
Fan Motor Quantity:	1

Air - Cooled Unit Performance

Release Date:	09-Sep-2016	Return Gas Temp. (°F):	40
Compressor:	ZS11KAE-TF5-118 x 1	Subcooling (°F):	5
Performance No:	12126	Air Flow Rate (CFM)	2050

90°F Ambient Air Temperature

<u>Evap Temp</u> (°F)	<u>Unit Capacity</u> (Btu/hr)	<u>Cond. Temp.</u> (°F)	<u>Temp. Diff.</u> (°F)	<u>EER</u> (Btu/Wh):
15	11,800	98.7	8.7	8.9
20	13,100	99.6	9.6	9.6
25	14,500	100.5	10.5	10.3