

ZB07KAE-TF5

HFC, R-134a, 60 Hz, 3 -Phase, 200/230 V
Medium Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	20	45
Condensing Temp. (°F)	120	130
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	120	130
Capacity (Btu/hr)	4430	7260
Power (W):	703	805
Current (Amps):	2.60	2.70
EER (Btu/Wh):	6.30	9.00
Mass Flow (lbs/hr):	70	126
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2018-01-31	

Mechanical

Displacment(in ³ /Rev):	1.02
Displacment(ft ³ /hr):	123.96
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	14.94
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	15.69 *
Suction Size (in),Type:	3/4 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	25
Oil Recharge (oz):	21
Net Weight (lbs):	44.0
Internal Free Volume (in ³):	122.0
Horse Power:	1.00

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	37.8
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	7.3
Max Operating Current(Amp):	4.1
RLA, MCC/1.4;use for contactor selection (Amp):	5.2
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	4.7
RPM:	3500
UL File No:	SA-2337
UL File Date:	2003-12-16

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	200/220	3	50	Medium Temperature
R-404A HFC	200/220	3	50	Medium Temperature
R-404A HFC	200/230	3	60	Medium Temperature
R-507 HFC	200/230	3	60	Medium Temperature
R-507 HFC	200/220	3	50	Medium Temperature
R-407C HFC	200/220	3	50	Medium Temperature
R-407C HFC	200/230	3	60	Medium Temperature
R-407A HFC	200/220	3	50	Medium Temperature
R-407A HFC	200/230	3	60	Medium Temperature
R-407F HFC	200/220	3	50	Medium Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407F HFC	200/230	3	60	Medium Temperature
R-448A HFO	200/220	3	50	Medium Temperature
R-448A HFO	200/230	3	60	Medium Temperature
R-449A HFO	200/220	3	50	Medium Temperature
R-449A HFO	200/230	3	60	Medium Temperature