

ZBD57KCE-TF5

HCFC, R-22, 60 Hz, 3 -Phase, 200/230 V
High Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	87500	56000
Power (W):	8400	7300
Current (Amps):	25.80	23.40
EER (Btu/Wh):	10.40	7.70
Mass Flow (lbs/hr):	1390	825
<u>Sound Data @</u>		
Sound Power (dBA):	83 Avg	88 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2013-07-17	

Mechanical

Displacment(in ³ /Rev):	7.50
Displacment(ft ³ /hr):	911.46
Overall Length (in):	9.67
Overall Width (in):	10.36
Overall Height (in):	18.94
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	19.69 *
Suction Size (in),Type:	1 1/4 Rotolo
Discharge Size (in),Type:	1 1/4 Rotolo
Initial Oil Charge (oz):	64
Oil Recharge (oz):	60
Net Weight (lbs):	95.0
Internal Free Volume (in ³):	345.0
Horse Power:	7.50

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*(Amp):	224.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	46.2
Max Operating Current(Amp):	32.1
RLA, MCC/1.4;use for contactor selection (Amp):	33.0
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	29.6
RPM:	3500
UL File No:	SA-2337
UL File Date:	1994-06-15

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	200/220	3	50	High Temp
R-134a HFC	200/230	3	60	High Temp
R-404A HFC	200/220	3	50	Medium Temperature
R-404A HFC	200/230	3	60	Medium Temperature
R-507 HFC	200/220	3	50	Medium Temperature
R-507 HFC	200/230	3	60	Medium Temperature
R-22 HCFC	200/220	3	50	High Temp
R-407C HFC	200/220	3	50	High Temp
R-407C HFC	200/230	3	60	High Temp
R-407A HFC	200/220	3	50	Medium Temperature

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407A HFC	200/230	3	60	Medium Temperature
R-407F HFC	200/220	3	50	Medium Temperature
R-407F HFC	200/230	3	60	Medium Temperature
R-448A HFO	200/220	3	50	Medium Temperature
R-448A HFO	200/230	3	60	Medium Temperature
R-449A HFO	200/220	3	50	Medium Temperature
R-449A HFO	200/230	3	60	Medium Temperature