

ZF15K4E-TFE

HFC, R-134a, 60 Hz, 3 -Phase, 575 V

High Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	20
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	130	120
Capacity (Btu/hr)	37800	24000
Power (W):	3770	2970
Current (Amps):	4.70	4.00
EER (Btu/Wh):	10.00	8.10
Mass Flow (lbs/hr):	655	383
<u>Sound Data @</u>		
Sound Power (dBA):	0 Avg	0 Max
Vibration mils(peak-peak):	0.0 Avg	0.0 Max
Record Date:	2005-05-03	

Electrical

LRA-High*(Amp):	50.0
LRA Low* (Amp):	
LRA-Half Winding (Amp):	
MCC (Amps):	11.0
Max Operating Current(Amp):	8.0
RLA, MCC/1.4;use for contactor selection (Amp):	7.9
RLA, MCC/1.56;use for breaker & wire size selection (Amp):	7.1
RPM:	3500
UL File No:	SA-2337
UL File Date:	1994-06-15
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.	

Mechanical

Displacment(in^3/Rev):	5.04
Displacment(ft^3/hr):	612.50
Overall Length (in):	9.67
Overall Width (in):	10.12
Overall Height (in):	17.40
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	18.15 *
Suction Size (in),Type:	7/8 Stub
Discharge Size (in),Type:	1/2 Stub
Initial Oil Charge (oz):	64
Oil Recharge (oz):	60
Net Weight (lbs):	80.0
Internal Free Volume (in^3):	354.0
Horse Power:	5.00
*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Capacitors

Alternate Applications

Refrigerant	Voltage	Phase	Freq (Hz)	Application
R-134a HFC	575	3	60	Medium Temp, Liquid Injected
R-134a HFC	575	3	60	Low Temp, Liquid Injected
R-404A HFC	575	3	60	Medium Temp, Liquid Injected
R-404A HFC	575	3	60	Low Temp, Low Condensing
R-404A HFC	575	3	60	Low Temp, Liquid Injected
R-507 HFC	575	3	60	Medium Temp, Liquid Injected
R-507 HFC	575	3	60	Low Temp, Low Condensing
R-507 HFC	575	3	60	Low Temp, Liquid Injected
R-407C HFC	575	3	60	UL Medium Temp
R-407C HFC	575	3	60	Low Temp, Liquid Injected

Alternate Applications

<u>Refrigerant</u>	<u>Voltage</u>	<u>Phase</u>	<u>Freq (Hz)</u>	<u>Application</u>
R-407C HFC	575	3	60	UL Low Temp
R-407A HFC	575	3	60	UL Medium Temp
R-407A HFC	575	3	60	UL Low Temp
R-407A HFC	575	3	60	Low Temp, Liquid Injected
R-407F HFC	575	3	60	Low Temp, Liquid Injected
R-448A HFO	575	3	60	Low Temp, Liquid Injected
R-448A HFO	575	3	60	Low Temp, Low Condensing
R-448A HFO	575	3	60	Medium Temp, Liquid Injected
R-449A HFO	575	3	60	Medium Temp, Liquid Injected
R-449A HFO	575	3	60	Low Temp, Liquid Injected
R-449A HFO	575	3	60	Low Temp, Low Condensing