ZP120KCE-TFD

HFC, R-410A, 60 Hz, 3 -Phase, 460 V

Air Conditioning

Production Status:



Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evaporator Temp. (°F)	45	35	
Condensing Temp. (°F)	130	120	
Return Gas Temp. (°F)	65	55	
Liquid Temp. (°F)	115	105	
Capacity (Btu/hr)	123000	109000	
Power (W):	11100	9760	
Current (Amps):	16.40	14.90	
EER (Btu/Wh):	11.10	11.20	
Mass Flow (lbs/hr):	1815	1525	
Sound Data @			
Sound Power (dBA):	79 Avg	84 Max	
Vibration mils(peak-peak):	3.0 Avg	4.5 Max	
Record Date:	2017-03-22		
1			

Electrical

Licotrical					
LRA-High*(Amp):	125.0				
LRA Low* (Amp):					
LRA-Half Winding (Amp):					
MCC (Amps):	28.0				
Max Operating Current(Amp):	22.0				
RLA, MCC/1.4;use for contactor selection (Amp):	20.0				
RLA, MCC/1.56;use for breaker & wire size selection (Amp)	: 17.9				
RPM:	3500				
UL File No: SA-2	e No: SA-2337				
UL File Date: 1996	-09-27				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Mechanical

Displacment(in^3/Rev):	6.93
Displacment(ft^3/hr):	842.19
Overall Length (in):	10.38
Overall Width (in):	11.23
Overall Height (in):	21.00
Mounting Length (in):	7.50
Mounting Width (in):	7.50
Mounting Height (in):	21.75 *
Suction Size (in),Type:	1 3/8 Stub
Discharge Size (in),Type:	7/8 Stub
Initial Oil Charge (oz):	110
Oil Recharge (oz):	106
Net Weight (lbs):	135.0
Internal Free Volume (in^3):	809.0
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Capacitors

Alternate Applications

Refrigerant	<u>Voltage</u>	<u>Phase</u>	Freq (Hz)	Application
R-410A HFC	380/420	3	50	Air Conditioning