

# Acrylic Latex Caulk with Silicone - White



## DiversiTech Acrylic Latex Caulk with Silicone

A mildew resistant, paintable sealant formulated to provide long lasting, flexible, weatherproof seals between most common building materials including wood, masonry, concrete, brick, drywall, metal and glass. Its smooth, creamy consistency makes **DiversiTech Acrylic Latex Caulk** easy to tool, and cures to a tough, flexible seal. It can be used for both interior and exterior applications.

### **Paintability:**

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

### **Directions:**

1. Clean and dry surface. Remove any soap, oil, or grease.
2. Fill deep joints or voids with solid filler to 1/2" of surface.
3. Cut nozzle to desired bead size; puncture inner seal. Insert cartridge into standard caulking gun.
4. For a smooth seal, hold at 45° angle and apply by pushing sealant ahead of nozzle.
5. Excess material can be smoothed with a putty knife or cleaned with a damp cloth.

### **Specifications:**

Meets or exceeds ASTM C-834.

### **Caution:**

Keep from freezing  
Do not take internally  
Keep out of reach of children

VOC 24 GPL

### **KEEP OUT OF REACH OF CHILDREN.**



**WARNING:** This product can expose you to chemicals including Acetaldehyde (CAS 75-07-0) which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

NET 10.3 FL. OZ. (305 ml)



0 95247 41546 5