

SDS# Triple-D-Gran
Date: October 2015

Total Pages: 5

Triple-D™ - Granular

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Triple-D Universal Coil Cleaner Granular
Catalog Number: Triple-D-Gran
Manufactured by: DiversiTech Corporation
6650 Sugarloaf Parkway
Duluth, GA, 30097
Information Phone No.: 1+678.542.3600
EMERGENCY Phone No.: 1 800.255.3924 Chem-Tel (Chemical Emergencies)
SDS DATE REVISED: 05/22/2015
PREPARED BY: V. Leone

SECTION 2. HAZARDOUS INGREDIENTS INFORMATION

GHS Classification:

Skin Irritation Category 1B
Eye Irritation Category 1
Specific Target Organ Toxicity - Single Exposure: Respiratory Tract Irritation Category 3

Label Elements:



Signal Word Danger!

Hazard Statement(s)

H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statement(s)

P102 Keep out of reach of children.
P103 Read label before use.
P233 Keep container tightly closed.
P260 Do not breathe dust, mist or spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear rubber, neoprene, or nitrile protective gloves/protective clothing and safety goggles or face shield for/eye protection/face protection.
P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse SKIN with water or shower.
P363 Wash contaminated clothing before reuse.
P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor.
P403 Store in a well-ventilated place.
P405 Store locked up.
P501 Dispose of contents and container to appropriate facility in accordance with Federal, State, and local regulations.

Triple-D™ - Granular

SECTION 3. HAZARDOUS INGREDIENTS INFORMATION

INGREDIENT	CAS No.	EINECS No.	% or Range	GHS Classification
Sodium Metasilicate	6834-92-0	229-912-9	20-40	H314: Acute Toxicity Category 4 H314: Skin Corrosion Category 1A H318: Eye Damage Category 1 H402: Aquatic Acute Category 3
Potassium Carbonate	584-08-7	209-529-3	20-40	H315: Skin Irritant Category 3 H319: Eye Irritant Category 2B H335: May cause respiratory irrit. Category 3

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Give large quantities of water if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse.

Eye Contact: water Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

4.2. Signs and Symptoms of Exposure:

Inhalation: Effects from inhalation of dust may cause serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may vary from mild to severe irritation, sneezing, sore throat or runny nose. Severe pneumonitis may occur.

Ingestion: Symptoms may include burns of mouth, throat, and stomach bleeding, vomiting, diarrhea, fall in blood pressure.

Skin Contact: Contact with skin can cause redness, irritation or severe burns and scarring with greater exposures.

Eye Contact: Contact with mist, spray or dust causes redness, severe irritation or burning in eyes. Prolonged exposures can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure: Prolonged contact with dilute solutions or mists has a destructive effect upon tissue.

SECTION 5. FIREFIGHTING MEASURES

Suitable and Unsuitable Extinguishing Media:

Use any means suitable for extinguishing surrounding fire.

Special Equipment and Precautions for Fire-Fighters:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece operated in the pressure demand or other positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment and clothing during clean-up.

Methods and Material for Containment and Clean-Up: Sweep up material and collect in a waterproof recovery container. Undamaged product may be recovered and used according to label instructions. Do not flush caustic residues to the sewer. Do not use aluminum tools to collect absorbed material or aluminum containers to store collected waste. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities (700 gallons) of this product. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. Remove contaminated clothing immediately.

Triple-D™ - Granular

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling: Keep in a tightly closed container. Protect from physical damage. Keep this and all chemicals out of the reach of children. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities: Store in a ventilated area. Store locked up. Containers of this material may be hazardous when empty since they retain product residues (dust). Containers of this material may be hazardous when empty since they retain product residues. Do not store with aluminum or magnesium. Do not mix with acids or organic materials.

Observe all warnings and precautions listed for the product.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Airborne Exposure Limits:

Sodium Metasilicate:

OSHA Permissible Exposure Limit (PEL): 2mg/m3 (for dust)

Appropriate Engineering Controls:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation. A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear rubber, neoprene, nitrile, Saranex® boots, gloves, lab coat, apron or coveralls, as necessary and appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities or a source of running water in the work area.

Work Hygienic Practices: Use proper industrial hygiene practices to minimize hazardous exposure. Wash hands after handling this material, and before eating, smoking or using the bathroom.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Granular orange solid
Odor:	Lavender
Odor Threshold:	Not established
pH @ 25°C:	None
Melting Point (Pour Point):	Not applicable
Boiling Point:	Not applicable
Flash Point:	Not established
Evaporation Rate (Water = 1):	Not applicable
Flammable Limits:	Not applicable
LEL:	N/A
UEL:	N/A
Vapor pressure (mm Hg):	Not applicable
Vapor Density (Air = 1):	Not applicable
Specific gravity (H2O = 1):	1.13
Solubility in water:	100%
Specific gravity (H2O = 1):	1.13
Octanol/Water Partition Coefficient:	Not available
Autoignition Temperature:	Not available
Decomposition Temperature:	Not available

Triple-D™ - Granular

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability: Stable under ordinary conditions of use and storage.

Possibility of Hazardous Reactions: Will not occur.

Conditions to Avoid: Extreme heat, incompatibles.

Incompatible Materials: Strong oxidizers, strong acids, and formaldehyde.

Hazardous Decomposition Products: If this product is involved in a fire, it may evolve into carbon monoxide, carbon dioxide, and other unidentified fragments.

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects:

Inhalation: Effects from inhalation of dust may cause serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may vary from mild to severe irritation, sneezing, sore throat or runny nose. Severe pneumonitis may occur.

Ingestion: Symptoms may include burns of mouth, throat, and stomach bleeding, vomiting, diarrhea, fall in blood pressure.

Skin Contact: Contact with skin can cause redness, irritation or severe burns and scarring with greater exposures.

Eye Contact: Contact with mist, spray or dust causes redness, severe irritation or burning in eyes. Prolonged exposures can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure: Prolonged contact with dilute solutions or mists has a destructive effect upon tissue.

Carcinogenic effects: Not classified

Teratogenicity/Reproductive toxicity: Not classified

Mutagenic effects: Not classified

Numerical Measures of Toxicity: None known

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity: No data available

Aquatic: No data available

Persistence and Degradability: No data available

Bioaccumulative Potential: No data available

Mobility in Soil: No data available.

Other Adverse Effects: None known

Other: For more information, see "[HANDBOOK OF ENVIRONMENTAL FATE AND EXPOSURE DATA.](#)"

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of spill clean-up and other wastes in accordance with Federal, State, and local regulations. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Treat empty containers as hazardous. Dispose of container and unused contents in accordance with federal, state and local requirements.

Triple-D™ - Granular

SECTION 14. TRANSPORTATION INFORMATION

UN Number: UN3262

Domestic Highway Transport:

DOT Hazard Label: ORM-D in quantities less than 2.2 lb or 1 KG

DOT Description: UN3262, Corrosive Solid, Basic, Inorganic, NOS (Sodium Metasilicate and Potassium Carbonate) 8, PGIII

IMO (Ocean Freight):

UN ID No.: UN3262

Shipping Name: Corrosive Solid, Basic, Inorganic, NOS (Sodium Metasilicate and Potassium Carbonate)

Class: 8

Packing group: III (Limited Quantity)

SECTION 15. REGULATORY INFORMATION

Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification is not required for this material.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III planning based on reporting is not required for quantities below 250 pounds.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III (for SARA 313). This material is not subject to reporting requirements.

Toxic Substances Control Act (TSCA) Status: All components are on the TSCA inventory.

Poison Schedule: WHMIS: Not applicable. This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION:

Revision Summary: All Sections: New GHS Format

SDS DATE REVISED: 10/12/2015

HMIS III Ratings

HMIS III®

Health	2
Flamability	0
Physical Hazard	0
Personal Protection	B

This information is, to the best of our knowledge and belief, accurate and reliable as of the date completed. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the completeness and suitability of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information, nor do we offer any warranty against patent infringement.