



Product Data Sheet



Description

Elgen's Notch Lock eliminates duct system noises and vibrations. This is done with an airtight flexible connection consisting of a fabric that attaches to sheet metal on both sides.

Elgen's Notch Lock Flexible Connector attaches to a fan source on one side and ductwork on the other.

Standard Construction

Formed with ASTM A-653 G60 material

	Vinlon (ZLL)	Neoprene (ZLN)	Hypalon (ZLH)
Temp Range	-40 F to 180 F	-40 F to 200 F	-50 F to 300 F
Color	Black	Black	White
Weight SQ/YD	22	32	24
Tear Strength	100/100	25/25	20/20
Tensile Strength	300/300	500/500	350/250
Features	High Tear Strength, High Abrasion, Low Smoke, Extremely Flexible	Airtight Resistance to Acids, Gasoline & Grease, General Purpose	Excellent Acid, Weather, UV, Mildew & Ozone Resistance, High Abrasion, Resistant to Grease

	Silguard (ZLSG)	Teflon (ZLTF)	40oz Neoprene (ZLN)	Super High Temp
Temp Range	-75 F to 500 F	-75 F to 500 F	-40 F to 285 F	-40 F to 1800 F
Color	White	Gray	Black	Gray/White
Weight SQ/YD	18	18	40	36
Tear Strength	50/40	60/40	17/12	60/60
Tensile Strength	200/150	400/300	630/465	480/330
Features	High Temp, Very Low Smoke, Flame, Water & Oil Resistant	High Temp & Acid Resistant, Best Overall Fabric		

Features

All Elgen fabrics are designed to meet NFPA-701 (formerly UL-214)

22 GA With 40 oz Neoprene Tested At 23" Positive Static Pressure

Elgen Vinlon fabric meets UL-723 and NFPA-701

All Elgen fabrics are designed to meet NFPA-90A and 90B

All fabrics are water proof and airtight to +/- 10" w.g.

All fabrics have flame retardant coatings

All items are Flame Resistant

Tested in accordance with LEEDS®

Requirements Meets SMACNA

Union Made

Optional Construction

G90

Stainless Steel 304

Stainless Steel 316

Aluminum

PCD

Galvanneal (Paint Grip)

Agion (Antimicrobial Coating)

Packaging

Size	Gauge	FT Per Box
All Sizes	24-26	100'

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624

Tel: 800.503.9805 :: Fax: 201.964.9030

info@elgenmfg.com :: www.elgenmfg.com