

ED SERIES



EXTERIOR DOOR FOR WALLS AND CEILINGS

Doors are fabricated from 16 gage, galvanized steel with a prime coat finish and 1" thick rigid foam insulation and neoprene gasket on four sides.

Frame are fabricated from 16 gage, galvanized steel with a prime coat finish. Door has a heavy duty spring to assure positive latching.

Frame is fabricated from 16 gage, galvanized steel with a prime coat finish and provided with bolt holes.

Hinge is concealed and operates completely out of sight, so that only the door and frame are visible.

Exterior Latch is a cylinder lock that features a knurled knob or key operation.

Finish is a prime coat suitable for painting.

FR SERIES



FIRE RATED WALL ACCESS DOORS

Doors are Fire Rated by Underwriters Laboratories Inc., for 1-1/2 hours, "B" Label, and meet ANSI-UL 10B standard. Door has a heavy duty spring closer to assure positive latching when panel closes. This door is for wall installation only.

Door and Frame are fabricated from 16 gage, galvanized steel with a prime coat finish. Door has a heavy duty spring to assure positive latching.

Frame is equipped with both masonry anchors and bolt holes to facilitate installation in all types of wall construction.

Concealed Hinge operates completely out of sight so that only the door and frame is visible.

Exterior Latch is recessed and is operated using a ring attached to the sliding bolt.

Interior Latch Release Slide is included enabling door to be opened from the inside.

Finish is a prime coat suitable for painting.

Optional Latch:

- CL- Cylinder Lock

Optional Finish:

- SS- Stainless Steel

FRC SERIES



FIRE RATED CEILING ACCESS DOORS

Doors are rated by Underwriters Laboratories for 1-1/2 hours, "B" label in walls, and by Warnock Hersey for 3 hours in ceilings and 2 hours in walls. Door should be utilized when providing access in fire rated walls and ceilings. Doors have heavy-duty spring closures to ensure positive latching when panel closes.

Door is fabricated from 20 gage, galvanized steel with a prime coat finish.

Door panel is provided with 2" of insulation in a sandwich type construction.

Frame is fabricated from 16 gage, galvanized steel with a prime coat finish and provided with masonry anchors and bolt holes.

Hinge is a fully concealed and mounted on the long side of the rectangular door panel.

Exterior Latch is a dual purpose lock that features a knurled knob and key operation. Both are provided at time of shipping.

Interior Latch Release Slide is included enabling door to be opened from the inside.

Option:

- MLP- Mortice Lock Prep