

# SIDE MOUNT UNDERCOUNTER REFRIGERATORS

## Side Mounted Condensing Unit

ET – Series • ETR1 • ETR2 • ETWR2 • ETR3



▲ ETR1



▲ ETR2



▲ ETWR2



▲ ETR3

### Cabinet Construction

Heavy duty stainless steel interior and exterior, with galvanized steel finished bottom and back wall of exterior. High quality 16 gauge stainless steel worktop, ABS evaporator drain cover. 2.5" thick high density foamed-in-place polyurethane insulation. Four 4" diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build-up.

### Refrigeration System

- Side mounted condensing unit for extra interior space compared to back mounted units
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with multiple evaporator fan motors provide balanced airflow throughout cabinet to ensure faster temperature drop
- Removable side panel and slide-out condensing unit for convenient repair and maintenance
- Removable condenser coil air filter for easy cleaning
- Environmentally friendly CFC free R-134A refrigerant
- Air defrost, time-initiated and terminated
- Copper tube and aluminum fin evaporator with anti-corrosive coating
- Energy efficient condensate drain pan assembly heated by high side copper tube
- Pressure relief ports for rapid re-entry
- Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

### Lighting

- Shielded incandescent interior lighting

### Doors

- Heavy duty stainless steel interior and exterior
- 2.5" thick foamed-in-place polyurethane insulation
- Rounded corners for a comfortable and hazard-free work space
- Heavy duty adjustable torsion spring self-closing door system
- One piece snap-in magnetic door gaskets for easy replacement
- Heavy duty recessed door handles for a flat surface
- Door locks

### Shelving

- Two epoxy coated wire shelves per section
- Stainless steel pilasters and shelf clips

### Temperature Control




- Factory preset temperature, 35°F
- Setting temperature range from 33°F to 54°F
- Easy to read digital temperature display
- Easy to program push-button temperature control
- Microchip digital control and monitoring system with a variety of functions to monitor and maintain optimum temperature

### Options


- 4" high stainless steel backsplash for worktop use
- 2 1/2" diameter casters (3 1/2" overall height)




## Dimensions




▲ ETR1



▲ ETR2



▲ ETWR2



▲ ETR3

Model	Ref/ Frz/ Dual	# of Doors	Capacity <sup>†</sup> (Cu.Ft.)	HP	Refrigerant	# of Shelves	BTU/HR <sup>†</sup>	Power (V-Hz-Ph)	Amps	Crated Weight (LBS)	Exterior Dimensions (Inches)		
											L	D	H*
ETR1	Ref	1	9	1/4+	R-134A	2	2,075	115-60-1	3.52	129	35 5/8	31 1/2	29 1/4
ETR2	Ref	2	13	1/4+	R-134A	4	2,075	115-60-1	3.52	268	47 1/2	31 1/2	29 1/4
ETWR2	Ref	2	18	1/4+	R-134A	4	2,075	115-60-1	3.52	320	59 1/4	31 1/2	29 1/4
ETR3	Ref	3	22	1/3	R-134A	6	2,555	115-60-1	5.24	353	71 1/8	31 1/2	29 1/4

\* : Height does not include 5" for casters.

Ref = Refrigerator

† : Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C).

Specifications subject to change without notice.

Product dimensions are for general purposes and not absolute value. Product capacity(†) is calculated based on standard industry figures. Slight variations may exist. If dimensions and capacity are critical, please contact Everest Refrigeration.



Please visit our website for updated Energy Efficiency information.