

Submittal Data: System 36RSLX ABU36RSLX & AOU36RLX



Job Name: _____ Location: _____

Purchaser: _____

Engineer: _____

Submitted To: _____ For: Reference Approval Construction

Submitted By: _____

Unit Designation: _____ Schedule No. _____ Model No.: _____

Capacities:

Cooling	34,100/36,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	95/75
Heating	38,200/42,700 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
SEER	14.0
EER <i>Clg/Htg</i>	8.1/10.4

Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L/</i>	48/45/41
Noise Level Heating <i>db (A) - H/ M/ L/</i>	48/43/39
Weight	106 lbs.

Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	30A
Min. Ampacity	23A
Running Current <i>Cooling</i>	18.3/18.8A
Running Current <i>Heating</i>	15.6/18.8A
Weight	141 lbs.

Refrigerant Piping:

Max Ht. Difference	98 ft.
Max Total or Combined Length	165 ft.
Discharge Vapor Line (O.D.)	3/8 in.
Suction (O.D.)	5/8 in.

Standard Features:

- ◆ Six year compressor warranty
- ◆ Two year parts warranty
- ◆ Wireless Remote Control
- ◆ Auto Louver: 4 Way
- ◆ Energy saver
- ◆ 24 Hour Timer
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ Auto Mode
- ◆ Fresh Air Intake
- ◆ Optional Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Cold Prevention
- ◆ Pump Down Operation

Notes:

OUTLINE AND DIMENSIONS

