

# Submittal Data: System 24RULX ABU24RULX & AOU24RLX



Job Name: \_\_\_\_\_ Location: \_\_\_\_\_

Purchaser: \_\_\_\_\_

Engineer: \_\_\_\_\_

Submitted To: \_\_\_\_\_ For:  Reference  Approval  Construction

Submitted By: \_\_\_\_\_

Unit Designation: \_\_\_\_\_ Schedule No. \_\_\_\_\_ Model No.: \_\_\_\_\_

### Capacities:

Cooling	22,200/27,300 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	95/75
Heating	24,200/29,000 BTU/h
Outdoor Design Temperature <i>F° DB/WB</i>	47/43
SEER	15.0
EER <i>Clg/Htg</i>	9.9/10.2

### Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L/</i>	47/43/38
Noise Level Heating <i>db (A) - H/ M/ L/</i>	47/43/38
Weight	62 lbs.

### Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	20A
Min. Ampacity	15.4A
Running Current <i>Cooling</i>	9.8/12.5A
Running Current <i>Heating</i>	10.2/12.5A
Weight	141 lbs.

### Refrigerant Piping:

Max Ht. Difference	66 ft.
Max Total or Combined Length	165 ft.
Discharge Vapor Line (O.D.)	3/8 in.
Suction (O.D.)	5/8 in.

### Standard Features:

- ◆ Six year compressor warranty
- ◆ Two year parts warranty
- ◆ Wireless Remote Control
- ◆ Auto Louver: 4 Way
- ◆ Energy saver
- ◆ 24 Hour Timer
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ Auto Mode
- ◆ Fresh Air Intake
- ◆ Optional Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Cold Prevention
- ◆ Pump Down Operation

### Notes:

---



---



---

### OUTLINE AND DIMENSIONS

