

Solstice[®] N40 (R-448A)

Technical Data Sheet



Introduction

Solstice® N40 (R-448A) is a zeotropic blend designed to serve as a replacement for R-404A/ R-507, R-22, R-407 series and interim blends in low- and medium-temperature commercial refrigeration. This hydrofluoro-olefin (HFO) blend demonstrates environmental and performance benefits in retrofits as well as new systems. In addition, Solstice N40 has been approved by major global equipment and component manufacturers.

Benefits

- Reduced GWP: 68% lower than R-404A
- 5%-15% lower energy consumption compared to R-404A
- Increased capacity versus R-404A

Applications

Low- and medium-temperature commercial DX refrigeration for both new equipment and retrofits:

- Supermarkets / Convenience stores: freezers, coolers, display cases
- Cold storage warehouses
- Self-contained condensing units

Physical Properties

Solstice® N40 (R-448A)	
Class/Type	Zeotropic blend
Formula	26%/26%/21%/7%/20% R-32/R-125/R-134a/ R-1234ze(E)/R-1234yf
Appearance	Colorless
ODP (ODP-R11=1)	0
GWP 4th/5th IPCC	1387 / 1273
Flammability Limits – ASTM E681-04 @ 21°C	Nonflammable
ASHRAE Std. 34 Safety Class	A1
LFL (% vol)	Nonflammable
Units	
Molecular weight	86.3 lbm/lbmol
Boiling temperature	-51.0°F
Critical temperature	180.8°F
Critical pressure	666.4 psia
Critical volume	0.03356 ft ³ /lbm
Critical density	29.80 lbm/ft ³
Vapor density at boiling point	0.2937 lbm/ft ³
Liquid density at 32°F	74.77 lbm/ft ³
Liquid density at 77°F	68.50 lbm/ft ³
Vapor density at 77°F	3.053 lbm/ft ³
Liquid heat capacity at 77°F	0.3717 Btu/lbm °R
Vapor heat capacity at 77°F	0.2767 Btu/lbm °R
Heat of vaporization at boiling point	103.9 Btu/lbm °R
Vapor pressure at 77°F	162.1 psia
Liquid thermal conductivity at 77°F	0.0469 Btu/h ft °R
Vapor thermal conductivity at 77°F	0.0084 Btu/h ft °R
Liquid viscosity at 77°F	9.34 x 10 ⁻⁵ lbm/ft s
Vapor viscosity at 77°F	8.41 x 10 ⁻⁶ lbm/ft s

Pressure and Temperature

Temp (°F)	Bubble	Dew (psig)	Average
-50	0.4	7.37	3.28
-45	2.50	3.93	0.03
-40	4.90	0.08	2.49
-35	7.50	2.1	4.80
-30	10.4	4.4	7.40
-25	13.5	7.0	10.3
-20	17	9.8	13.4
-15	20.8	13	16.9
-10	24.9	16.4	20.7
-5	29.4	20.2	24.8
0	34.2	24.3	29.3
5	39.4	28.8	34.1
10	45.1	33.6	39.4
15	51.2	38.9	45.1
20	57.8	44.6	51.2
25	64.8	50.7	57.8
30	72.3	57.3	64.8
35	80.4	64.4	72.4
40	89	72.1	80.6
45	98.2	80.3	89.3
50	108	89	98.5
55	118.4	98.4	108.4
60	129.4	108.4	118.9
65	141.1	119	130.1
70	153.5	130.3	141.9
75	166.6	142.4	154.5
80	180.5	155.1	167.8
85	195.1	168.7	181.9
90	210.5	183	196.8
95	226.7	198.2	212.5
100	243.7	214.3	229.0
105	261.6	231.3	246.5
110	280.5	249.2	264.9
115	300.2	268.1	284.2
120	320.9	288.1	304.5
125	342.6	309.1	325.9
130	365.3	331.3	348.3
135	389	354.7	371.9
140	413.8	379.3	396.6

Blue Values = inches mercury vacuum

Materials Compatibility

Honeywell does not recommend the use of chlorinated solvents to clean refrigeration systems or components.

Desiccants

Desiccant driers compatible with Solstice® N40 (R-448A) are commercially available.

Individual drier manufacturers should be contacted for specific recommendations.

Lubricants

Polyol ester (POE) oil is recommended for Solstice N40.

Compressor manufacturers typically qualify specific lubricants for use with their products. Users should check with the equipment manufacturer for the recommended lubricants for their system.

Plastics and Elastomers

Solstice N40 is compatible with most common materials. In the case of retrofit systems that may contain chlorinated materials, please contact your Honeywell sales representative for specific information.

Safety and Storage

Honeywell recommends reading the Safety Data Sheet (SDS) before using Solstice N40. According to the compressed gas classification, Solstice N40 is nonflammable. It has similar storage and handling requirements to R-404A in bulk and cylinder.

Package Sizes

Solstice N40 is available in 25lb disposable and 100lb refillable cylinders. For other packaging sizes please contact Honeywell distribution network.

Leak Detection

Leak detectors can be used for pinpointing specific leaks or for monitoring an entire room on a continual basis. Leak detection is important for refrigerant conservation, equipment protection and performance, reduction of emissions and protection of those coming in contact with the system. Customers should consult the equipment manufacturer for appropriate detectors.

Available Tools

Genepro Simulation software

Honeywell's refrigerants modelling software is a free download that eliminates the guesswork involved in selecting a refrigerant by allowing refrigeration engineers to run simulations based on actual data. The tool runs property calculations of refrigerants, conducts thermodynamic evaluations of air conditioning and refrigeration cycles, and provides a first principle thermodynamic comparison of new alternative refrigerants for retrofit applications or new system designs. Download the Genepro Refrigerants Modelling Software at <https://www.honeywell-refrigerants.com/americas/genetron-properties-suite/>

Smart Phones Apps

Download Honeywell PT chart ruler application for iOS and Android free.




Literature

Honeywell has a wide range of literature available for Solstice N40 including brochures, technical data sheet, retrofit guidelines and case studies.



Pressure and Enthalpy Solstice® N40 (R-448A)



For more information:

www.honeywell-refrigerants.com
or send an email to
refrigerants@honeywell.com

Although Honeywell International Inc. believes that the information contained herein is accurate and reliable, it is presented without guarantee or responsibility of any kind and does not constitute any representation or warranty of Honeywell International Inc., either expressed or implied. A number of factors may affect the performance of any products used in conjunction with user's materials, such as other raw materials, application, formulation, environmental factors and manufacturing conditions among others, all of which must be taken into account by the user in producing or using the products. The user should not assume that all necessary data for the proper evaluation of these products are contained herein. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liabilities (including, but not limited to, risks relating to results, patent infringement, regulatory compliance and health, safety and environment) related to the use of the products and/or information contained herein.

Solstice is a registered trademark of Honeywell International Inc.

Honeywell Refrigerants

115 Tabor Road
Morris Plains, NJ 07950
Phone: 1-800-631-8138



Version 1.5 | 01/2017
© 2017 Honeywell International Inc. All rights reserved.

Honeywell