



Indigo™ Series 522 Ice Cube Machine

Model: ☐ IR-0520A ☐ ID-0522A ☐ IY-0524A ☐ IR-0521W ☐ ID-0523W ☐ IY-0525W

to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate. • Space-Saving Design – Up to 485 lbs. (220 kgs.)

Designed for operators who know that ice is critical

- daily ice production and only 22" (55.88 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **DuraTech™ Exterior** provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available **LuminIce™ Growth Inhibitor** controls the growth of bacteria and yeast within the foodzone.

COMMERCIAL WARRANTY ICE MAKER **EVAPORATOR** COMPRESSOR YEAR YEAR PARTS PARTS AND LABOR

Specifications

BTU Per Hour:

5,300 (average) 6,100 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Ice Machine Flectric

Indigo Series i-522 Ice Machine on B-420 Bin

115/60/1 standard. (208-230/60/1 and 230/50/1 also available)

Minimum circuit ampacity:

Air-cooled: 14.4 1ph Water-cooled: 13.5 1ph

Maximum fuse size:

20 1ph Air-cooled: Water-cooled: 20 1ph

Ice Shape



Half Dice 3%" x 11%" x 7%" (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)



Regular 11/8" x 11/8" x 7/8" (2.86 x 2.86 x 2.22 cm)













COMPANY WITH QUALITY SYSTEM

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-522 on B-420 bin Storage Bin 24.50" (62.23 cm) (A) Electrical Entrance (2) Options (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units) 1/2" (1.27 cm) Auxillary Base Drain Socket © 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain G 3/4" (1.91 cm) Bin Drain 44.00" (111.7 cm) 6.00" (15.24 cm) **Installation Note** Minimum installation 34.00" (86.30 cm) clearance: Top/sides: 12" (30.50 cm) Back: 5" (12.7 cm)

Space-Saving Designs



	I-522 B-420	1-522 B-400*	
Height	71.50" 181.61 cm	59.50" 151.13 cm	
Width	22.00" 55.88 cm	30.00" 76.20 cm	
Depth	34.00" 86.30 cm	34.00" 86.30 cm	
Bin Storage	310 lbs. 140.7 kgs.	290 lbs. 131.7 kgs.	

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Specifications

			Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F	Water Usage/100 lbs. 45.4 kgs. of Ice	ENERGY STAR*
Model	lce Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	Potable Water			
AIR-COOLED	IR-0520A	regular	415 lbs.	290 lbs.	7.23	23.8 Gal.	
			188 kgs.	132 kgs.		90.1 L	
	ID-0522A dice	dice	475 lbs.	335 lbs.	6.64	23.8 Gal.	
<u>R</u> -C	ID-0322A		215 kgs.	152 kgs.		90.1 L	
A	IY-0524A half-dice	half-dice	485 lbs.	360 lbs.	6.45	23.8 Gal.	
			220 kgs.	163 kgs.		90.1 L	
ID-05	ID OF 21W	IR-0521W regular	395 lbs.	350 lbs.	5.19	23.8 Gal.	NA
	IN-U321VV		179 kgs.	159 kgs.		90.1 L	
	ID-0523W dice	460 lbs.	375 lbs.	5.09	23.8 Gal.	NA	
			209 kgs.	170 kgs.	3.09	90.1 L	NA
	IY-0525W half-dice	480 lbs.	395 lbs.	4.87	23.8 Gal.	NA	
			218 kgs.	179 kgs.	4.07	90.1 L	INA

Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 190 gal/ 719 L. * Water-cooled models are excluded from ENERGY STAR qualification.

Order ice storage bin separately.

Accessories

LuminIce™ **Growth Inhibitor** reduces yeast and

bacteria growth for a cleaner ice machine.

Allows ice bin level to be automatically



Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



AuCS®

schedules and performs routine ice machine cleaning automatically.



2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com



^{*} K-00141 bin adapter required.