




Indigo™ Series 1000 Ice Cube Machine

Model: DID-1002A DIY-1004A DID-1003W DIY-1005W DID-1092N DIY-1094N



• Space-Saving Design – Up to 1,020 lbs. (463 kgs.) daily ice production and only 30" (76.20 cm) wide.

and programmability make your ice machine easy to

own and less expensive to operate.

- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- DuraTech™ Exterior provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce™ Growth Inhibitor controls the growth of bacteria and yeast within the foodzone.





Ice Machine Electric

208-230/60/1 standard (208-230/60/3 and 230/50/1 also available.)

Minimum circuit ampacity:

Air-cooled: 13.5 1ph 9.5 3ph Water-cooled: 9.7 1ph 8.5 3ph 9.5 3ph Remote: 10.7 1ph

Maximum fuse size:

15 3ph Air-cooled: 20 1ph Water-cooled: 15 1ph 15 3ph Remote: 15 1ph 15 3ph

Specifications

BTU Per Hour:

16,250 (average) 18,600 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Ice Shape



Half Dice (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)













= ISO 9001:2008 =



Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-1000 on B-570 Storage Bin ② Electrical Entrance (2) Options ③ 38' (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) ⑤ 1/2' (1.27 cm) F.P.T. Lee Making Water Inlet ⑤ 3/8' (0.95 om) F.P.T. Lee Making Water Inlet ⑥ 1/2' (1.27 cm) F.P.T. Lee Making Water Inlet ⑥ 3/4' (1.91 cm) Bin Drain Installation Note Minimum installation clearance: Top/sides: 8" (20.32 cm); Back is 5" (12.7 cm)

Space-Saving Designs





	i-1000 B-570	i-1000 B-970*		
Height	76.50" 194.30 cm	76.50" 194.30 cm		
Width	30.00" 76.20 cm	48.00" 121.92 cm		
Depth	34.00" 86.30 cm	34.00" 86.30 cm		
Bin Storage	430 lbs. 195 kgs.	710 lbs. 322.2 kgs.		

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Specifications

		. Ice Productio		on 24 Hours	Power Usage kWh/100 lbs. @90°Air/70°F		Water Usage/ 100 lbs. 45.4 kgs. of Ice	ENERGY	
	Model	Ice Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	3 Ph	Potable Water	STAR*	
AIR-COOLED	ID-1002A	dice	990 lbs.	735 lbs.	5.41	5.41	19.8 Gal.	*	
			449 kgs.	333 kgs.			75.0 L		
	IY-1004A	half-dice	1,010 lbs.	745 lbs.	5.36	5.36	19.8 Gal.	*	
		10	458 kgs.	338 kgs.			75.0 L		
WATER-COOLED	ID-1003W	dice	1,000 lbs.	855 lbs.	4.23	4.23	19.8 Gal.	- NA	
			454 kgs.	388 kgs.			75.0 L		
	IY-1005W	half-dice	1,010 lbs.	870 lbs.	4.07	4.07	19.8 Gal.	NA	
		10	458 kgs.	395 kgs.			75.0 L		
/M	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 180 gal/681 L. * Water-cooled models are excluded from ENERGY STAR qualification.								
REMOTE- COOLED	ID-1092N dice	dice	960 lbs.	725 lbs.	5.50	5.50	19.8 Gal.	*	
			435 kgs.	329 kgs.			75.0 L		
	IY-1094N half-dice	1,020 lbs.	775 lbs.	5.28	5.28	19.8 Gal.	_		
			463 kgs.	352 kgs.	3.20	3.20	75.0 L		

Order ice storage bin separately. Ice storage bin and JC-0895 remote condenser must be ordered separately. Consult remote condenser specification sheet for details. To order 3 phase add "3" suffix to model # (ID-1002A3).

Accessories

LuminIce™ Growth Inhibitor reduces yeast and

reduces yeast and bacteria growth for a cleaner ice machine.



Bin Level Control Allows ice bin level to be automatically set. Built-in LED light



Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



AuCS®

schedules and performs routine ice machine cleaning automatically.



4772 (replaces 2707E S-1000) © 2011 Manitowoc 1/11 Continuing product improvement may necessitate change of specifications without

2110 South 26th Street
PO Box 1720
Manitowoc, WI 54221-1720 USA

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com

illuminates bin.



^{*}K-00370 bin adapter required.