# S-Series 500 Ice Cube Machine









#### **ANITATION**

We've made it simple to clean



#### **AVINGS**

The perfect balance of power and efficiency



#### עמטט

Designed to run whisper-quiet



### ERVICEABILITY

Easy access means less downtime

- Up to 540 lbs. (245 kgs.) daily ice production
- Only 30" (76.20 cm) wide
- Removable water distribution tube with no tools
- Food zone designed with soft, round, cove corners
- Patented cleaning and sanitizing technology
- Select components made with AlphaSan anti-microbial

- Hinged front door for easy access
- Warranty

5-year parts and 5-year labor coverage on ice machine evaporator 5-year parts and 3-year labor coverage on ice machine compressor 3-year parts-and-labor coverage on all other ice machine, dispenser, and storage bin components





Ice Cube & Flake Machines • Ice Storage Bins • Ice Dispensers



## **Manitowoc S-Series 500**

		lce producti	Ice production 24 hours								
Model	Cube size	lbs.	kgs.	kWh/100 lbs.							
SD-0502A	dice	400	181	6.4							
SD-0503W	SD-0503W dice 480 218 4.9										
SY-0504A	SY-0504A half-dice 400 181 6.4										
SY-0505W	SY-0505W half-dice 480 218 4.9										
REI	MOTE AIR-CO	OLED WITH J	C-0495A CON	IDENSER							
SD-0592N	dice	460	209	6.4							
SY-0594N half-dice 460 209 6.4											
Water usage/100 lbs./45.4 kgs. of Ice											
Pota	ble Water: 18 gallons,	68 liters • Water-coole	ed Condenser: 138 gallo	ons, 522 liters							

Order ice storage bin separately. "A" or "W" following model number indicates "Air" or "Water" condensing unit. Ice storage bin and JC-0495A remote condenser must be ordered separately. Consult remote condenser specification sheet for details.



Certified in Accordance with ARI Automatic Commercial Ice-Cube Machines (Batch-Type) Certification Program, which is based on ARI Standard 810

#### Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available.)

Min. circuit ampacity: Air-cooled — 13

Water-cooled — 12.3, Remote — 14.1

Max. fuse size: Air-cooled, Water-cooled, Remote — 20 amps HACR-type circuit breakers can be used in place of fuses.

#### **Specifications**

#### **BTU Per Hour:**

7,000 (average) 9,600 (peak)

#### Compressor:

Nominal rating: 3/4 HP

#### **Cupra-Nickel Condenser:**

(Water-cooled models) Adds protection from corrosive water elements.

#### **Operating Limits:**

· Ambient Temperature Range: Air and water:

35° to 110°F (1.6° to 43.3°C) Remote: -20° to 120°F (-29° to 49°C)

- · Water Temperature Range: 35° to 90°F (1.6° to 32.2°C)
- Water Pressure Ice Maker Water In:

Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

· Condenser Inlet Water In: (Water cooled only) Min. 20 psi (137.9 kPA) Max. 150 psi (1,034.2 kPA)



#### Air Flow Top View



#### AuCS@SI Accessory

Automatic Cleaning System purchased factory installed in the machine or as an option for field retrofits.


#### 2 Cube Sizes Available



**Half Dice** (.95 x 2.86 x 2.22 cm)




Dice <sup>7</sup>/8" x <sup>7</sup>/8" x <sup>7</sup>/8" (2.22 x 2.22 x 2.22 cm)



†Production for Dice and Half Dice cubes. Data is published for 60 Hz machines. 50 Hz machines produce approximately 7% less ice.

Space-Saving Designs		S-500 B-400	S-500 B-570
0110	Height	59.50" 151.13 cm	71.50" 181.61 cm
	Width	30.00" 76.20 cm	30.00" 76.20 cm
	Depth	34.00" 86.30 cm	34.00" 86.30 cm
	Bin Storage	290 lbs. 131.7 kgs.	430 lbs. 195.2 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). For comparison purposes multiply ARI capacity by 1.3 (30%) to arrive at approximate "Application Rating Capacity." "K-00214 bin adapter required.



**Installation Note - Minimum Installation Clearance: Top/Sides are 8" (20.32 cm),** Back is 5" (12.7 cm).




MANITOWOC ICE, INC. 2110 South 26th Street, P.O. Box 1720 Manitowoc, WI 54221-1720, USA Ph: 920-682-0161 • Fax: 920-683-7589 Visit us online at www.manitowocice.com





3'04 Continuing product improvement may necessitate change of specifications without notice ©2004 Manitowoc 2830

# **Ice Storage Bins**











Ice Cube & Flake Machines • Ice Storage Bins • Ice Dispensers



# **Manitowoc Ice Storage Bins**

	B-STYLE																								
Bin	Cap	acity	Fits Ice Machine Series Indicated														Dimensions								
Model	Lbs.	Kgs.	300	322	422	450	500	600	850	1000	1200	1400	1400C	1600	1800	QDual	QC/QF		Height		Width	Depth			
B-170	150	68	•	3	3	•	•										3	25"	63.50 cm	30"	76.20 cm	29.50"	74.92 cm		
B-320	210	95		•	•												•	38"	96.52 cm	22"	55.88 cm	34"	86.36 cm		
B-400	290	132	•	3	3	•	•	•	•	•	•						3	38"	96.52 cm	30"	76.20 cm	34"	86.36 cm		
B-420	310	141		•	•												•	50"	127 cm	22"	55.88 cm	34"	86.36 cm		
B-570	430	195	•	3	3	•	•	•	•	•	•						3	50"	127 cm	30"	76.20 cm	34"	86.36 cm		
B-970	710	323	1			1	1	2	2	2	2	•	2	•	•	2		50"	127 cm	48"	121.92 cm	34"	86.36 cm		

Soft durometer trim around opening helps silence bin door closing. Patent-pending hinge pin design holds bin door open while in use. Internal scoop holder stays above ice line for easy access and better sanitation. Stainless steel exterior is durable, corrosion resistant, and attractive.

1 K-00369 adapter required 2 K-00370 adapter required

3 K-00368 adapter required

One set of stainless steel legs included. Adjustable from 6.00" to 7.75" (15.24 to 20.32 cm). Included with bin.

Storage capacity is based on 80% of total volume x 30 lb/ft<sup>3</sup> average density of ice.





With ARI Ice Storage Bins Certification Program, which is based on ARI Standard 820

	$ extstyle{C-S}$ tyle																		
Bin	Capacity Fits Ice Machine Series Indicated Dimensions																		
Model	Lbs.	Kgs.	300	322	422	450	500	600	850	1000	1200	1400C	QC/QF		Height		Width	D	epth
C-730S	560	254	4	5	5	4	4	4	4	4	4	4	5	46"	116.84 cm	42"	106.68 cm	31.50"	80.01 cm

C-Style stainless steel exterior metal is same material used for S-Series ice machines. Bin door, although rectangular, is gray ABS to match S-Series ice machine trim color. C-Style bin does not include scoop holder, bin door design, or rounded corner enhancements included with S-Style or B-Style design. Bin leg is bullet design, adjustable from 6.00" to 7.75" (15.24 cm to 19.685 cm) and painted black. Bin liner is one-piece (seamless) "rotocast" polyethylene. Liner won't rust, dent, chip, crack or discolor.

4C-730 includes K-00023 adapter to mount 30" ice machine.

5 K-00117 adapter required.

Gray painted 6.00" (15.24 cm) bullet legs included, adjustable from 6.00" to 7.00" (15.24 to 17.78 cm).

Storage capacity is based on 80% of total volume x 30 lb/ft<sup>3</sup> average density of ice.





Certified In Accordance With ARI Ice Storage Bins Certification Program, which is based on ARI Standard 820

	B-Style Large Capacity																			
Bin	Capa	Capacity Fits Ice Machine Series Indicated Dimensions																		
Model	Lbs.	Kgs.	450	500	600	850	1000	1200	1400	1400C	1600	1800	QDual	QF2300	Н	leight		Width		Depth
B-750	748	339	•	•	•	•	•	•					•	•	57.00"	144.8 cm	30"	76.20 cm	34"	86.36 cm
B-1050	1,053	478	•	•	•	•	•	•					•	•	77.00"	195.6 cm	30"	76.20 cm	34"	86.36 cm
B-1100	1,114	505	•	•	•	•	•	•	•	•	•	•	•	•	56.00"	142.3 cm	48"	121.92 cm	34"	86.36 cm
B-1400	1,416	642	•	•	•	•	•	•	•	•	•	•	•	•	56.00"	142.3 cm	60"	152.40 cm	34"	86.36 cm

Manitowoc B-Style, large capacity ice storage bins are equipped with an ice gate for increased employee safety, easier ice removal, and reduced spillage.

Choose between a B-750 and B-1050, two of the smallest footprint, large capacity ice storage bins offered. Also available are the 48" wide B-1100 with 1,114 lbs. of ice storage capacity or the 60" wide model B-1400 with 1,416 lbs. of ice storage capacity. (B-1100; specify for use with 1-30" wide or 1-48" wide ice machine and B-1400 specify for use with 1-30" wide, 2-30" wide or 1-48" wide ice machine at time of purchase).

#### **Bin Leg Options**

4" (10.16 cm), 6" (15.24 cm) and 12" (30.48 cm) adjustable legs in painted and stainless steel and 2.5" (6.35 cm), and 7.625" (19.37cm) casters available for most models. Contact factory for model number and order information.

#### Warranty

Provides comprehensive, 3-year partsand-labor coverage. For details, see Ice Storage Bin Warranty Statement. B-750, B-1050, B-1100 and B-1400 provide a limited lifetime warranty on base, bin liner, and poly snout.

ICE MACHINE DEFLECTORS REQUIRED										
S-Series 450, 500, 600, 850, 1000, 1200	K-00347									
S-Series 1400, 1600, 1800	K-00349									
1400C and Q-Dual	K-00212 for side-by-side ice machines K-00211 for one ice machine									

Stainless steel 6.00" (15.24 cm) legs included, adjustable from 6.00" to 7.50" (15.24 to 19.05 cm).

Storage capacity is based on p0% of total volume x 30 lb/ft<sup>3</sup> average density of ice.







Certified In Accordance With ARI Ice Storage Bins Certification Program, which is based on ARI Standard 820



MANITOWOC ICE, INC.
2110 South 26th Street, P.O. Box 1720
Manitowoc, WI 54221-1720, USA
Ph: 920-682-0161 • Fax: 920-683-7589
Visit us online at www.manitowocice.com

2718C ©2005 Manitowoc 8/05 Continuing product improvement may necessitate change of specificati