

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Eco-Spray Adhesive
- **Article number:** 22-22
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture:** Adhesive.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Mon-Eco Industries, Inc.  
5 Joanna Ct.  
East Brunswick, NJ 08816  
Phone: 732-257-7942
- **1.4 Emergency telephone number:**  
ChemTel Inc.  
+1 (800)255-3924, +1 (813)248-0585



MON-ECO INDUSTRIES, INCORPORATED

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Classifications listed are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.  
The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361, H320.  
Eye Irritation 2B      H320      Causes eye irritation.



Repr. 2 H361: Suspected of damaging fertility or the unborn child.



flame

Flam. Liq. 2      H225      Highly flammable liquid and vapour.



health hazard

Repr. 2      H361fd-H362      Suspected of damaging fertility. Suspected of damaging the unborn child. Route of exposure: Inhalation. May cause harm to breast-fed children.

(Cont'd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 1)

STOT RE 2      H373      May cause damage to the central nervous system and the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1      H304      May be fatal if swallowed and enters airways.



environment

Aquatic Chronic 2      H411      Toxic to aquatic life with long lasting effects.



Skin Irrit. 2      H315      Causes skin irritation.

STOT SE 3      H336      May cause drowsiness or dizziness.

· **Additional information:**

There are no other hazards not otherwise classified that have been identified.  
0 % of the mixture consists of component(s) of unknown toxicity.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**

The following pictogram(s) are only for use within Europe: GHS09.



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Hexanes  
toluene  
cyclohexane

· **Hazard statements**

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.

H361: Suspected of damaging fertility or the unborn child.

H225      Highly flammable liquid and vapour.

H315      Causes skin irritation.

H361fd-H362 Suspected of damaging fertility. Suspected of damaging the unborn child. Route of exposure: Inhalation. May cause harm to breast-fed children.

H336      May cause drowsiness or dizziness.

H373      May cause damage to the central nervous system and the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

(Cont'd. on page 3)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

(Cont'd. from page 2)

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- P260 Do not breathe mist/vapours/spray.

- P280 Wear protective gloves / eye protection.

- P273 Avoid release to the environment.

- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

- P403+P235 Store in a well-ventilated place. Keep cool.

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

\* - Indicates a long term health hazard from repeated or prolonged exposures.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 110-54-3 Index number: 601-007-01-4	Hexanes Flam. Liq. 2, H225 Acute Tox. 4, H332	25-50%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	10-25%

(Cont'd. on page 4)

# Safety Data Sheet






according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 3)

CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1	cyclohexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Skin Irrit. 2, H315; STOT SE 3, H336	2,5-10%
CAS: 61788-76-9 EINECS: 263-004-3	Alkanes, chloro  Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Lact., H362	2,5-10%

**Additional information:**

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret.  
For the wording of the listed Hazard Statements refer to section 16.

## SECTION 4: First aid measures

**4.1 Description of first aid measures**
**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Rinse out mouth and then drink plenty of water.

A person vomiting while laying on their back should be turned onto their side.

Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Breathing difficulty

Dizziness

Coughing

Irritant to skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

**Hazards**

Danger of pulmonary oedema.

Danger of impaired breathing.

(Cont'd. on page 5)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 4)

Danger of convulsion.  
 Danger of disturbed cardiac rhythm.  
 Vapours may cause drowsiness and dizziness.  
 Causes damage to organs through prolonged or repeated exposure.

· **4.3 Indication of any immediate medical attention and special treatment needed**

Contains toluene.  
 May cause neurotoxic effects.  
 If swallowed or in case of vomiting, danger of entering the lungs.  
 Monitor circulation, possible shock treatment.  
 If necessary oxygen respiration treatment.  
 Medical supervision for at least 48 hours.  
 Later observation for pneumonia and pulmonary oedema.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
 Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
 Wear self-contained respiratory protective device.  
 Wear fully protective suit.
- **Additional information**  
 Eliminate all ignition sources if safe to do so.  
 Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Use respiratory protective device against the effects of fumes/dust/aerosol.  
 Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation  
 Keep away from ignition sources.  
 Protect from heat
- **6.2 Environmental precautions:**  
 Do not allow to enter sewers/ surface or ground water.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Prevent from spreading (e.g. by damming-in or oil barriers).
- **6.3 Methods and material for containment and cleaning up:**  
 Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).  
 Ensure adequate ventilation.  
 Dispose contaminated material as waste according to section 13.  
 Used rags or other cleaning materials should be soaked with water and placed in a sealed container.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.

(Cont'd. on page 6)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 5)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Use only in well ventilated areas.

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

Keep receptacles tightly sealed.

### · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

### · 7.2 Conditions for safe storage, including any incompatibilities

#### · Storage:

#### · Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

#### · Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

#### · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

#### · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### 110-54-3 Hexanes

IOELV (EU)	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm
PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm
TLV (USA)	Long-term value: 176 mg/m <sup>3</sup> , 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m <sup>3</sup> , 50 ppm

(Cont'd. on page 7)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: **Eco-Spray Adhesive**

(Cont'd. from page 6)

**108-88-3 toluene**

PEL (USA)	Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm

**110-82-7 cyclohexane**

IOELV (EU)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
PEL (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 300 ppm
REL (USA)	Long-term value: 1050 mg/m <sup>3</sup> , 300 ppm
TLV (USA)	Long-term value: 344 mg/m <sup>3</sup> , 100 ppm
EL (Canada)	Long-term value: 100 ppm
EV (Canada)	Long-term value: 100 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:****110-54-3 Hexanes**

BEI (USA)	0,4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis
-----------	---

**108-88-3 toluene**

BEI (USA)	0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

(Cont'd. on page 8)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

(Cont'd. from page 7)

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Pregnant women should strictly avoid inhalation or skin contact.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

Suitable respiratory protective device recommended.

Use suitable respiratory protective device when high concentrations are present.

NIOSH or EN approved organic vapour respirator equipped with a dust/mist prefilter should be used.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment**

No further relevant information available.

- **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Colour:	Amber coloured

- **Odour:** Mild

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	65 °C (149 °F)

(Cont'd. on page 9)



## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

(Cont'd. from page 8)

· <b>Flash point:</b>	-17 °C (1 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Auto/Self-ignition temperature:</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not self-igniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1,2 Vol %
<b>Upper:</b>	6,9 Vol %
· <b>Vapour pressure at 20 °C (68 °F):</b>	160 hPa (120 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0,77 g/cm <sup>3</sup> (6,426 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density at 20 °C (68 °F)</b>	3 (AIR = 1)
· <b>Evaporation rate at 20 °C (68 °F)</b>	8 (N-Butyl Acetate= 1)
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Keep away from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions**  
Highly flammable liquid and vapour.  
Reacts violently with oxidising agents.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.  
Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**  
Keep ignition sources away - Do not smoke.  
Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide

(Cont'd. on page 10)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

Hydrocarbons  
Hydrogen chloride (HCl)

(Cont'd. from page 9)

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Slight irritant effect on eyes.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**  
Suspected of damaging fertility or the unborn child. Route of exposure: Inhalation.  
Toxic and/or corrosive effects may be delayed up to 24 hours.
- **Acute effects (acute toxicity, irritation and corrosivity):** Vapours have narcotic effect.
- **Repeated dose toxicity:**  
May cause damage to the central nervous system and the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.  
Repeated exposure may cause skin dryness or cracking.  
May cause neurotoxic effects.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging fertility. Suspected of damaging the unborn child. Route of exposure: Inhalation.  
May cause harm to breast-fed children.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to the central nervous system and the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** Toxic for aquatic organisms
- **12.2 Persistence and degradability** No further relevant information available.

(Cont'd. on page 11)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 10)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms  
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT**

UN1133	Product is additionally classified as a MARINE POLLUTANT based on MARPOL and DOT rules. Labeling as a MARINE POLLUTANT is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.
--------	--
- **ADR, IMDG, IATA**

UN1133	
--------	--

(Cont'd. on page 12)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

(Cont'd. from page 11)

· **14.2 UN proper shipping name**



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

· **DOT, IATA**

Adhesives

· **ADR**

1133 ADHESIVES, ENVIRONMENTALLY  
HAZARDOUS

· **IMDG**

ADHESIVES, MARINE POLLUTANT

· **14.3 Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids.

· **Label**

3

· **ADR**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **DOT, ADR, IMDG, IATA**

II

· **14.5 Environmental hazards:**

Product contains environmentally hazardous  
substances: cyclohexane, Alkanes, chloro

(Cont'd. on page 13)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

Trade name: Eco-Spray Adhesive

(Cont'd. from page 12)

· <b>Marine pollutant:</b>	Yes
· <b>Special marking (ADR):</b>	Symbol (fish and tree) Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	33
· <b>EMS Number:</b>	F-E,S-D
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
· <b>IATA</b>	Limited quantity by air: 1L
· <b>UN "Model Regulation":</b>	UN 1133 ADHESIVES, 3, II

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· <b>Section 355 (extremely hazardous substances):</b>
--

None of the ingredients are listed.
-------------------------------------

· <b>Section 313 (Specific toxic chemical listings):</b>
--

110-54-3	Hexanes
----------	---------

110-82-7	cyclohexane
----------	-------------

108-88-3	toluene
----------	---------

· <b>TSCA (Toxic Substances Control Act):</b>
---

All ingredients are listed.
-----------------------------

· <b>Proposition 65 (California):</b>
---------------------------------------

· <b>Chemicals known to cause cancer:</b>
---

Present in trace quantities.
------------------------------

106-99-0	1,3-butadiene buta-1,3-diene
----------	------------------------------

· <b>Chemicals known to cause reproductive toxicity for females:</b>
--

108-88-3	toluene
----------	---------

106-99-0	1,3-butadiene buta-1,3-diene
----------	------------------------------

· <b>Chemicals known to cause reproductive toxicity for males:</b>
--

Present in trace quantities.
------------------------------

106-99-0	1,3-butadiene buta-1,3-diene
----------	------------------------------

(Cont'd. on page 14)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 13)

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
106-99-0	1,3-butadiene buta-1,3-diene

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

110-54-3	Hexanes	II
110-82-7	cyclohexane	I
108-88-3	toluene	II

· **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

110-54-3	Hexanes
108-88-3	toluene
110-82-7	cyclohexane

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I**

None of the ingredients are listed.

· **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients are listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.

(Cont'd. on page 15)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and OSHA  
GHS

Printing date 19.11.2015

Revision: 19.11.2015

**Trade name: Eco-Spray Adhesive**

(Cont'd. from page 14)

H361d Suspected of damaging the unborn child. Route of exposure: Inhalation.

H362 May cause harm to breast-fed children.

H373 May cause damage to the central nervous system and the nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Lact.: Reproductive toxicity, Additional category, Effects on or via lactation

Repr. 2: Reproductive toxicity, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

**Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)