

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Eco-Duct Seal (Gray)**
- **Article number: 44-52**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Adhesive.
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Mon-Eco Industries, Inc.
5 Joanna Ct.
East Brunswick, NJ 08816
Phone: 732-257-7942
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585



MON-ECO INDUSTRIES, INCORPORATED

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.
The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.
Classifications listed also are applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200).



Repr. 2 H361: Suspected of damaging fertility or the unborn child.



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

| | | |
|-------------|--------|--|
| Repr. 2 | H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. Route of exposure: Inhalative. |
| STOT RE 2 | H373 | May cause damage to the central nervous system through prolonged or repeated exposure. |
| Asp. Tox. 1 | H304 | May be fatal if swallowed and enters airways. |

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 1)



environment


Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.




Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

• **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 Xn; Harmful

R48/20-62-63-65: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of impaired fertility. Possible risk of harm to the unborn child.
Harmful: may cause lung damage if swallowed.

 Xi; Irritant

R38: Irritating to skin.



N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

• **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

• **2.2 Label elements**

• **Labelling according to Regulation (EC) No 1272/2008**

The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: H361.

The product is additionally classified and labelled according to the Globally Harmonized System within the United States (GHS).

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.

The product is classified and labelled according to the CLP regulation.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 2)

- **Hazard pictograms**



This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS02 GHS07 GHS08 GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

toluene
n-hexane
cyclohexane
titanium dioxide

- **Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H361fd, H411.

The following Hazard Statements are applicable only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H361.

H361: Suspected of damaging fertility or the unborn child.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. Route of exposure: Inhalative.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314 Get medical advice/attention if you feel unwell.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard description:**

- **WHMIS-symbols:**

B2 - Flammable liquid

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014


Trade name: Eco-Duct Seal (Gray)

(Contd. of page 3)

D2A - Very toxic material causing other toxic effects



- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

| | | |
|------------|---|----------------|
| HEALTH | 2 | Health = *2 |
| FIRE | 3 | Fire = 3 |
| REACTIVITY | 0 | Reactivity = 0 |

* - Indicates a long term health hazard from repeated or prolonged exposures.

- **HMIS Long Term Health Hazard Substances**

| | |
|------------|------------------|
| 110-54-3 | Hexanes |
| 108-88-3 | toluene |
| 110-54-3 | n-hexane |
| 13463-67-7 | titanium dioxide |

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|----------------------------|---|--------|
| CAS: 110-54-3 | Hexanes | 10-25% |
| Index number: 601-007-01-4 | Xn R20-48; F R11 Flam. Liq. 2, H225 Acute Tox. 4, H332 | |

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

| | | (Contd. of page 4) |
|--|---|---|
| CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3 | toluene Xn R48/20-63-65; Xi R38; F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336 | 10-25% |
| CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 | cyclohexane Xn R65; Xi R38; F R11; N R50/53 R67 Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Irrit. 2, H315; STOT SE 3, H336 | < 5% |
| CAS: 71011-25-1 EINECS: 275-125-9 | Alkyl Quaternary ammonium bentonite Xi R36 Eye Irrit. 2, H319 | < 5% |
| CAS: 119-47-1 EINECS: 204-327-1 | 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol T Repr. Cat. 2 R61; Xn R62 Repr. 2, H361 | < 1% |
| · Dangerous Components (Alternative Classifications): | | |
| CAS: 13463-67-7 EINECS: 236-675-5 | titanium dioxide (classification relevant for USA/Canada only) Carc. 2, H351 | < 1% |
| · Additional information: For the wording of the listed risk phrases refer to section 16. | | |
| · Notable Trace Components (0,1% w/w) | | |
| CAS: 1333-86-4 EINECS: 215-609-9 | Carbon black | Xn R40 Carc. Cat. 3 Carc. 2, H351 |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 5)

If skin irritation is experienced, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while laying on their back should be turned onto their side.

- **4.2 Most important symptoms and effects, both acute and delayed**

Headache

Breathing difficulty

Dizziness

Coughing

Irritant to skin and mucous membranes.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

- **Hazards**

Danger of pulmonary oedema.

Danger of impaired breathing.

Danger of convulsion.

Danger of disturbed cardiac rhythm.

Vapours may cause drowsiness and dizziness.

Causes damage to organs through prolonged or repeated exposure.

- **4.3 Indication of any immediate medical attention and special treatment needed**

May produce a cardiotoxic /hemotoxic effect.

Contains toluene.

May cause neurotoxic effects.

If swallowed or in case of vomiting, danger of entering the lungs.

Monitor circulation, possible shock treatment.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Later observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information**

Eliminate all ignition sources if safe to do so.

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

Cool endangered receptacles with water spray.

(Contd. of page 6)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

· 6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Dispose contaminated material as waste according to item 13.

Used rags or other cleaning materials should be soaked with water and placed in a sealed container.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Rags, metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed metal container rated for flammable waste.

Keep receptacles tightly sealed.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

Keep container tightly sealed.

(Contd. of page 7)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.· **8.1 Control parameters**· **Ingredients with limit values that require monitoring at the workplace:**

110-54-3 Hexanes

| | |
|-------------|--|
| IOELV (EU) | Long-term value: 72 mg/m ³ , 20 ppm |
| PEL (USA) | Long-term value: 1800 mg/m ³ , 500 ppm |
| REL (USA) | Long-term value: 180 mg/m ³ , 50 ppm |
| TLV (USA) | Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI |
| EL (Canada) | Long-term value: 20 ppm Skin |
| EV (Canada) | Long-term value: 176 mg/m ³ , 50 ppm |

108-88-3 toluene

| | |
|-------------|---|
| PEL (USA) | Long-term value: 200 ppm Ceiling limit: 300; 500* ppm *10-min peak per 8-hr shift |
| REL (USA) | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV (USA) | Long-term value: 75 mg/m ³ , 20 ppm BEI |
| EL (Canada) | Long-term value: 20 ppm R |
| EV (Canada) | Long-term value: 20 ppm |

110-54-3 n-hexane

| | |
|-------------|--|
| IOELV (EU) | Long-term value: 72 mg/m ³ , 20 ppm |
| PEL (USA) | Long-term value: 1800 mg/m ³ , 500 ppm |
| REL (USA) | Long-term value: 180 mg/m ³ , 50 ppm |
| TLV (USA) | Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI |
| EL (Canada) | Long-term value: 20 ppm Skin |
| EV (Canada) | Long-term value: 176 mg/m ³ , 50 ppm |

110-82-7 cyclohexane

| | |
|------------|---|
| IOELV (EU) | Long-term value: 700 mg/m ³ , 200 ppm |
| PEL (USA) | Long-term value: 1050 mg/m ³ , 300 ppm |
| REL (USA) | Long-term value: 1050 mg/m ³ , 300 ppm |

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 8)

| | |
|-------------|--|
| TLV (USA) | Long-term value: 344 mg/m ³ , 100 ppm |
| EL (Canada) | Long-term value: 100 ppm |
| EV (Canada) | Long-term value: 100 ppm |

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.

· **Ingredients with biological limit values:**

110-54-3 Hexanes

| | |
|-----------|---|
| BEI (USA) | 0,4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis |
|-----------|---|

108-88-3 toluene

| | |
|-----------|--|
| BEI (USA) | 0,02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0,03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0,3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

110-54-3 n-hexane

| | |
|-----------|---|
| BEI (USA) | 0,4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis |
|-----------|---|

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Pregnant women should strictly avoid inhalation or skin contact.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Suitable respiratory protective device recommended.
Use suitable respiratory protective device when high concentrations are present.

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 9)

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

· **Risk management measures**

See Section 7 for additional information.

No further relevant information available.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Pasty

Colour: Grey

· **Odour:** Mild

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Not Determined.

Boiling point/Boiling range: 150 ° F /65 °C

· **Flash point:** < 0° F/ < -18 °C

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 10)

- **Auto/Self-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Self-igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 1,2 Vol %
 - Upper:** 6,9 Vol %
- **Vapour pressure at 20 °C:** 160 hPa
- **Density at 20 °C:** 1,04 g/cm³
- **Relative density:** Not determined.
- **Vapour density at 20 °C:** 3 (AIR = 1)
- **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
- **VOC content:** 34,3 %
- **9.2 Other information:** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Keep away from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions**
 - Flammable.
 - Reacts violently with oxidising agents.
 - Used empty containers may contain product gases which form explosive mixtures with air.
 - Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
 - Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**
 - Keep ignition sources away - Do not smoke.
 - Store away from oxidising agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
 - Carbon monoxide and carbon dioxide

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

Hydrocarbons

(Contd. of page 11)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

108-88-3 toluene

| | | |
|------------|---------|----------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4h | 5320 mg/l (mouse) |

110-82-7 cyclohexane

| | | |
|------|------|-------------------|
| Oral | LD50 | 12705 mg/kg (rat) |
|------|------|-------------------|

Primary irritant effect:

• **on the skin:** Irritant to skin and mucous membranes.

• **on the eye:** Slight irritant effect on eyes.

• **Sensitisation:** No sensitising effects known.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Suspected of damaging fertility or the unborn child. Route of exposure: Inhalative. Route of exposure: Inhalative.

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 24 hours.

• **Acute effects (acute toxicity, irritation and corrosivity):** Vapours have narcotic effect.

Repeated dose toxicity:

May cause damage to organs through prolonged or repeated exposure.

Repeated exposure may cause skin dryness or cracking.

May cause neurotoxic effects.

• **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**

Repr. 2

SECTION 12: Ecological information

12.1 Toxicity

• **Aquatic toxicity:** Toxic for aquatic organisms

• **12.2 Persistence and degradability** No further relevant information available.

• **12.3 Bioaccumulative potential** No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

Ecotoxicological effects:

• **Remark:** Toxic for fish

(Contd. on page 13)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 12)

- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA** UN1993
- **14.2 UN proper shipping name**
- **DOT** Flammable liquids, n.o.s. (HEXANES, TOLUENE)
- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (HEXANES, TOLUENE), ENVIRONMENTALLY HAZARDOUS
- **IMDG** FLAMMABLE LIQUID, N.O.S. (HEXANES, TOLUENE), MARINE POLLUTANT
- **IATA** FLAMMABLE LIQUID, N.O.S. (HEXANES, TOLUENE)
- **14.3 Transport hazard class(es)**
- **DOT**
- **Class** 3 Flammable liquids.



(Contd. on page 14)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 13)

· Label

3

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG



· Class

3 Flammable liquids.

· Label

3

· IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· DOT, ADR, IMDG, IATA

II

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances: cyclohexane

· Marine pollutant:

Yes

· Special marking (ADR):

Symbol (fish and tree)

· 14.6 Special precautions for user

Symbol (fish and tree)

· Danger code (Kemler):

Warning: Flammable liquids.

· EMS Number:

33

· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

F-E, S-E

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

· Tunnel restriction code

D/E

(Contd. on page 15)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 14)

- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN "Model Regulation":** UN1993, FLAMMABLE LIQUID, N.O.S. (HEXANES, TOLUENE), ENVIRONMENTALLY HAZARDOUS, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

110-54-3 Hexanes

108-88-3 toluene

110-82-7 cyclohexane

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

- **Chemicals known to cause reproductive toxicity for females:**

108-88-3 toluene

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

110-54-3 Hexanes II

108-88-3 toluene II

110-54-3 n-hexane II

110-82-7 cyclohexane I

- **IARC (International Agency for Research on Cancer)**

108-88-3 toluene 3

9003-55-8 styrene-butadiene latex 3

(Contd. on page 16)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 15)

| | | |
|--|------------------|----|
| 13463-67-7 | titanium dioxide | 2B |
| · TLV (Threshold Limit Value established by ACGIH) | | |
| 108-88-3 | toluene | A4 |
| 13463-67-7 | titanium dioxide | A4 |
| · NIOSH-Ca (National Institute for Occupational Safety and Health) | | |
| 13463-67-7 | titanium dioxide | |
| · Canada | | |
| · Canadian Domestic Substances List (DSL) | | |
| All ingredients are listed. | | |
| · Canadian Ingredient Disclosure list (limit 0.1%) | | |
| None of the ingredients are listed. | | |
| · Canadian Ingredient Disclosure list (limit 1%) | | |
| 110-54-3 | Hexanes | |
| 108-88-3 | toluene | |
| 110-54-3 | n-hexane | |
| 110-82-7 | cyclohexane | |
| · Other regulations, limitations and prohibitive regulations | | |
| This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations. | | |
| · Substances of very high concern (SVHC) according to REACH, Article 57 | | |
| None of the ingredients are listed. | | |
| · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out. | | |

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalative.
H361d Suspected of damaging the unborn child. Route of exposure: Inhalative.
H373 May cause damage to the central nervous system through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
R20 Harmful by inhalation.
R36 Irritating to eyes.

(Contd. on page 17)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
OSHA GHS

Printing date 21.10.2014

Revision: 21.10.2014

Trade name: Eco-Duct Seal (Gray)

(Contd. of page 16)

- R38 Irritating to skin.
- R48 Danger of serious damage to health by prolonged exposure.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R61 May cause harm to the unborn child.
- R62 Possible risk of impaired fertility.
- R63 Possible risk of harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R67 Vapours may cause drowsiness and dizziness.

• **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- WHMIS: Workplace Hazardous Materials Information System (Canada)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Repr. 2: Reproductive toxicity, Hazard Category 2
- Repr. 2: Reproductive toxicity, Hazard Category 2
- Repr. 2: Reproductive toxicity, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

• **Sources**

- SDS Prepared by:
- ChemTel Inc.
- 1305 North Florida Avenue
- Tampa, Florida USA 33602-2902
- Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
- Website: www.chemtelinc.com