

Model: **CTO-EK10**
Part #: 300-08035

REPLACEMENT CARTRIDGE

ITEM #: _____ QTY: _____

JOB NAME/NUMBER _____

Snapshot

The **CTO-EK10** is a compatible replacement cartridge for the Everpure® quick-change filter cartridges. It is a 15" quick-change cartridge that reduces sediment down to 0.5 micron and reduces chlorine, taste & odor at a flow rate of 1.7 gpm for 18,000 gallons. The cartridge will fit single or multiple (combination) cartridge systems as a replacement for the listed filter models.



Cartridge Benefits

- Improves the quality and consistency of cold and hot beverages.
- Reduces maintenance frequency and cost, and extends equipment life.
- Gradient-density sediment filtration protects against dirt, rust and other debris down to 0.5 microns.
- High-capacity activated-carbon filtration makes water taste great and protects equipment against corrosive chlorine.

Application

- Replacement cartridge for Everpure® MC, XC, 4FC, 4FC-5, 4CB-5, 7FC, 7FC-5, 7CB-5 cartridges.
- Capacity and flow of filters vary, calculate filter replacement frequency accordingly.

Installation Tips

- No activation procedure or flushing is required for cartridge to perform as specified.
- Insure cartridge is designed to replace the existing cartridge.
- Do not exceed cartridge specifications for temperature and pressure.
- Allow 3" clearance below system for filter cartridge removal and replacement.
- Feed-water connection to system should be COLD only.



It is recommended that filters be changed every 12 months, when capacity is reached or when effluent pressure or flow becomes inadequate.

This product is for commercial use only and must be installed and maintained according to manufacturer's guidelines.

Do not use on water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Dealer/Distributor Info:

OptiPure, a division of AQUION
2605 Technology Dr., Bldg 300 Plano, TX 75074
p: 972.881.9797; f: 972.422.6262
e: info@optipure.net www.optipurewater.com

► Specifications

Cartridge	
Dimensions (Height x Width x Depth, inches)	14.7" x 3.9" x 3.9"
Operating Pressure Range	10-125 psi (0.7 -8.6 bar)
Inlet Water Temperature Range	35 - 100°F (2 - 38°C)
Shipping Weight	5 lbs.
Performance	
Chlorine, Taste and Odor Reduction Capacity	18,000 gals. (68,137 liters)
Service Flow Rate	1.7 gpm (6.4 lpm)
Sediment Reduction	0.5 micron (nominal)
Scale & Corrosion Inhibitor	N/A

► Replaces Everpure Cartridges

Model	Part Number
MC	9612-56
XC	9613-10
4CB-5	9617-16
4FC-5	9693-21
4FC	9692-21
7CB-5	9618-11
7FC-5	9693-61
7FC	9692-61

► Warranty

OptiPure Cartridges are warranted against defects in material and workmanship up to one year or when cartridge capacity is reached. Claims of capacity or rated service life are not applicable for mechanical filtration. For complete warranty information, contact OptiPure customer service.