

ARCHITECTURAL SPECIFICATIONS PANASONIC ADVANCED VENTILATION SERIES



CEILING MOUNTED 190 CFM VENTILATION FAN

FV-20VQ3 WhisperCeiling Ventilating fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 190 CFM and no more than 0.8 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge(w.g.) and with no less than 144 CFM no more than 1.4 sone as certified by HVI at 0.25 w.g. Power Consumption shall be no greater than 42 watts at 0.1 w.g. and 42 watts at 0.25 w.g. ENERGY STAR rated with efficiency of no less than 4.5 CFM/watt at 0.1 w.g. and 3.4 CFM/watt at 0.25 w.g. The motor shall be totally enclosed, four pole condenser type engineered to operate continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 6". Fan shall be UL and cUL listed for tub/ shower enclosure when used with GFCI branch circuit wiring. Fan shall be ASHRAE 62.2, LEED, ENERGY STAR IAP, EarthCraft, California Title-24, and WA Ventilation Code compliant.

FV-30VQ3 WhisperCeiling

Ventilation fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 290 CFM and no more than 2.0 sones as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure WG. Power consumption shall be no greater than 64 watts with efficiency rating of no less than 4.5 CFM/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be 6". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring.