

ARCHITECTURAL SPECIFICATIONS PANASONIC ADVANCED VENTILATION SERIES



CEILING MOUNTED 290 CFM VENTILATION FAN

Ventilating fan shall be of the ceiling mount, Energy conserving vent type, with no less than 290 CFM and no more than 2.0 sones as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge (w.g.) and with no less than 257 CFM as certified by HVI at 0.25 w.g. Power Consumption shall be no greater than 64 watts at 0.1 w.g. and 62 watts at 0.25 w.g. ENERGY STAR rated with efficiency of no less than 4.5 CFM/watt at 0.1 w.g. and 4.1 CFM/watt at 0.25 w.g. The motor shall be totally enclosed, four pole condenser type engineered to operate continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 6". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Fan shall be ASHRAE 62.2, LEED, ENERGY STAR IAP, EarthCraft, California Title-24, and WA Ventilation Code compliant.

FV-30VQ3 WhisperCeiling

Ventilation fan shall be of the ceiling mount, ENERGY STAR rated type, with no less than 290 CFM and no more than