

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATIONS AND OF THE COMPANY UNDERTAKING**

**Product Name** Polyken 44 Spray Adhesive  
**Product Description** Spray Adhesive  
**Manufacturer/Supplier** Berry Plastics Corporation, Tapes and Coatings Division  
**Address** 25 Forge Parkway  
Franklin, MA 02038  
**Phone Number** (800) 248-7659 (Monday – Friday 8:00 am to 5:00 pm)  
**Chemtrec Number** (800) 424-9300  
**Revision Date:** August 30, 2012  
**MSDS Date:** August 29, 2005

*Safety Data Sheet according to EC directive 2001/59/EC and OSHA's Hazcom Standard (29 CFR 1910.1200)*

**2. HAZARDS IDENTIFICATION**

**EU Main Hazards**

R11 Highly flammable.  
R36/38 Irritating to eyes and skin.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R62 Possible risk of impaired fertility.  
R65 Harmful: may cause lung damage if swallowed.  
R67 Vapours may cause drowsiness and dizziness.

**Routes of Entry**

Absorption - Eye contact - Ingestion - Inhalation - Skin contact

**Carcinogenic Status**

Not considered carcinogenic by NTP, IARC, and OSHA.

**Target Organs**

Central Nervous System - Skin - Eye - Liver - Kidney - Respiratory System - Reproductive

**Health Effects - Eyes**

Liquid, mist or vapor may cause pain, transient irritation and superficial corneal effects.

**Health Effects - Skin**

Material may cause irritation. Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Material can be absorbed through the skin and cause effects similar to those resulting from inhalation.

**Health Effects - Ingestion**

Swallowing may have the following effects:

- abdominal pain - vomiting - central nervous system depression - kidney damage - liver damage – testis damage – aspiration into the lungs may occur during ingestion or vomiting causing lung damage

A large dose may have the following effects:

- systemic effects similar to those resulting from inhalation

---

## 2. HAZARDS IDENTIFICATION

---

### Health Effects - Inhalation

Exposure to vapor may have the following effects:

- irritation of nose, throat and respiratory tract - central nervous system depression - dizziness - drowsiness - headache - mental confusion

Exposure to vapor at high concentrations may have the following effects:

- nerve damage leading to numbness and muscle weakness - lung damage - liver damage - kidney damage - testis damage

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

Component Name	CAS#/Codes	Concentration	R Phrases	Classification
Hexane	110-54-3 203-777-6	<25.0%	R11, R38, R48/20, F; Xn; N R62, R65, R67, R51/53	
Acetone	67-64-1 200-662-2	<30.0%	R11, R36, R66, R67	F; Xi
Propane	74-98-6 200-827-9	<20.0%	R12	F+
Dimethyl Ether	115-10-6 204-065-8	<15.0%	R12	F+
Polymers and Resins	N.A.	<10.0%	None	None

---

## 4. FIRST AID MEASURES

---

### Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

### Skin

Immediately flood the skin with large quantities of water for at least 15 minutes, preferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed or dry-cleaned before re-use. Obtain medical attention if blistering occurs or redness persists.

### Ingestion

Do not induce vomiting. Have victim drink 1-3 glasses of water to dilute stomach contents. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

### Inhalation

Remove from exposure. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

### Advice to Physicians

Mineral oil, baby oil, makeup remover or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.

---

## 5. FIRE - FIGHTING MEASURES

---

### Extinguishing Media

Use foam, dry chemical or carbon dioxide. Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

### Unusual Fire and Explosion Hazards

Vapors can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware of possibility of re-ignition. For aerosol products – exposure to temperature over 130°F may cause containers to burst and release highly flammable gas.

---

## 5. FIRE - FIGHTING MEASURES

---

### Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal. Wear appropriate protective clothing. Eliminate all sources of ignition. Use non-sparking scoops for flammable materials. Vapors can accumulate in low areas. Consider need for evacuation. Prevent the material from entering drains or watercourses. Notify authorities if spill has entered watercourse or sewer or has contaminated soil or vegetation.

---

## 7. HANDLING AND STORAGE

---

Keep from reach of children. Do not puncture, incinerate or place aerosol product containers in compactors. Use in well ventilated area. Use local exhaust ventilation. Avoid inhaling vapor. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use. Do not flame cut, braze or use welding torch on container. Intentional misuse by deliberately concentrating or inhaling the vapors from this product may be harmful or fatal.

Store away from sources of heat or ignition. Storage area should be: - cool - dry - well ventilated - away from incompatible materials - out of direct sunlight - away from sources of ignition (heat, sparks, flames, pilot lights) Do not store above 120°F.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational Exposure Standards

Exposure limits are listed below, if they exist.

#### Hexane

ACGIH: TLV 50ppm (176mg/m<sup>3</sup>) 8h TWA. (skin)

OSHA: PEL 500ppm (1800) mg/m<sup>3</sup>) 8h TWA.

Can be absorbed through skin.

#### Acetone

ACGIH: TLV 500ppm (1188mg/m<sup>3</sup>) 8h TWA.

ACGIH (STEL): 750 ppm (1782 mg/m<sup>3</sup>) 15min.

OSHA: PEL 1000ppm (2400 mg/m<sup>3</sup>) 8h TWA.

#### Propane

ACGIH: TLV 1000 ppm (varies) 8h TWA.

OSHA: PEL 1000ppm (1800 mg/m<sup>3</sup>) 8h TWA.

#### Dimethyl Ether

None Established

### Engineering Control Measures

Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions.

### Respiratory Protection

Respiratory protection if there is a risk of exposure to high vapor concentrations. The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

### Hand Protection

Butyl gloves are recommended.

### Eye Protection

Chemical goggles or safety glasses with side shields

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Body Protection

If there is danger of splashing, wear: - overall or apron

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Physical State	Liquid
Color	White
Odor	Mint like
pH	Not applicable
Specific Gravity	0.7526
Boiling Range/Point (°C/F)	-42 to 70.5 (-44 to 159)
Melting Point (°C/F)	Not determined
Flash Point (PMCC) (°C/F)	-104/-156
Vapor Pressure	Not determined
Evaporation Rate	Faster than butyl acetate
Solubility in Water	Negligible
Vapor Density (Air = 1)	Heavier than air
Viscosity (cSt)	Not determined
Lower Explosive Limit/Upper Explosive Limit	1.0%/18.0%
VOC (g/l)	378 g/l total product (491 g/l less water and exempt)
VOC (% by weight)	54.1% total product

---

## 10. STABILITY AND REACTIVITY

---

### Stability

Stable under normal conditions.

### Conditions to Avoid

Heat, sparks, flames - High temperatures – sources of ignition – welding arcs – pilot lights – static electricity

### Materials to Avoid

Strong oxidizing agents - acids - bases - reducing agents

### Hazardous Polymerization

Will not occur.

### Hazardous Decomposition Products

Oxides of carbon - acetic acid - oxides of sulfur - oxides of nitrogen - various hydrocarbons

---

## 11. TOXICOLOGICAL INFORMATION

---

### Acute Toxicity

Acetone: Oral LD50 rat 5800 mg/kg

Dermal LD50 rabbit 20,000 mg/kg

Dimethyl Ether: LC50 rat 308.5 mg/l 4hr

### Specific Target Organ Systemic Toxicity (single and repeat)

May cause adverse effects to the liver, kidney, and central nervous system.

### Serious Eye damage/Eye Irritation

May cause irritation.

---

## 11. TOXICOLOGICAL INFORMATION

---

### **Skin Corrosion/Irritation**

May cause irritation.

### **Respiratory or Skin Sensitization**

This product is not expected to cause skin or respiratory sensitization.

### **Carcinogenicity**

Not considered carcinogenic by NTP, IARC, and OSHA.

### **Germ Cell Mutagenicity**

Hexane: Negative for mutagenicity in the Ames and the mouse lymphoma assays, with and without metabolic activation.

### **Toxicity to Reproduction**

Hexane: In animal studies permanent testicular damage has been observed.

---

## 12. ECOLOGICAL INFORMATION

---

### **Mobility**

No relevant studies identified.

### **Persistence/Degradability**

Hexane: Readily biodegradable

### **Bio-accumulation**

No relevant studies identified.

### **Ecotoxicity**

Acetone: LC50 Rainbow trout (*Oncorhynchus mykiss*) 96 h 5,540 mg/l

EC50 *Daphnia magna* 48 h 7,635 mg/l

Hexane: LC50 Rainbow trout (*Oncorhynchus mykiss*) 96 h 12.51 mg/l

EC50 *Daphnia magna* 48 h 21.85 mg/l

---

## 13. DISPOSAL CONSIDERATIONS

---

Dispose of in accordance with all applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near to the container. Use non-sparking tools. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

---

## 14. TRANSPORT INFORMATION

---

**DOT CFR 172.101 Data** Consumer Commodity, ORM-D (US ground shipment only)

**UN Proper Shipping Name** Aerosols

**UN Class** (2.1)

**UN Number** UN1950

**UN Packaging Group** None

**Classification for AIR Transportation (IATA)** Consult current IATA Regulations prior to shipping by air.

---

## 15. REGULATORY INFORMATION

---

<b>EU Label Information</b>
-----------------------------

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments(2001/60/EC and 2006/8/EC)

### **EU Hazard Symbol and Indication of Danger**

Xn - Harmful

N - Dangerous for the environment

F - Highly flammable

---

**15. REGULATORY INFORMATION**

---

**R phrases**

R11 Highly flammable.

R36/38 Irritating to eyes and skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

**S phrases**

S 9 Keep container in a well-ventilated place.

S16 Keep away from sources of ignition. - No smoking.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S33 Take precautionary measures against static discharges.

S36/37 Wear suitable protective clothing and gloves.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**US REGULATIONS (Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS**

**TSCA Listing**

All ingredients have been verified for inclusion on the EPA Toxic Substance Control Act Chemical Substance Inventory.

**EINECS Listing**

All ingredients in this product have not been verified for inclusion on the European Inventory of Existing Commercial Chemical Substances (EINECS) or specifically exempted.

**DSL (Canadian) Listing**

All ingredients in this product have been verified for inclusion on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL).

**WHMIS Classification**

B5.D2A

This product was classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations and the MSDS contains all the information required by these regulations.

**California Proposition 65**

This product does not contain materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

**SARA Title III Sect. 302 (EHS)**

This product does not contain any chemicals subject to SARA Title III Section 302.

**SARA Title III Sect. 304**

The following chemicals have reportable quantities: - Hexane (110-54-3) 5000# – Acetone (67-64-1) 5000# - Propane (74-98-6) – Dimethyl ether (115-10-6)

**SARA Title III Sect. 311/312 Categorization**

Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard, Fire Hazard, Sudden Release of Pressure

**SARA Title III Sect. 313**

This product contains a chemical that is listed in Section 313 at or above de minimis concentrations. The following listed chemicals are present: Hexane (110-54-3)

---

**16. OTHER INFORMATION**

---

**NFPA Ratings**

NFPA Code for Flammability - 4  
NFPA Code for Health - 2  
NFPA Code for Reactivity - 0  
NFPA Code for Special Hazards – None

**HMIS Ratings**

HMIS Code for Flammability - 4  
HMIS Code for Health - 2  
HMIS Code for Reactivity - 0  
HMIS Code for Personal Protection - See Section 8

**Abbreviations**

N/A: Denotes no applicable information found or available  
CAS#: Chemical Abstracts Service Number  
ACGIH: American Conference of Governmental Industrial Hygienists  
OSHA: Occupational Safety and Health Administration  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
STEL: Short Term Exposure Limit  
NTP: National Toxicology Program  
IARC: International Agency for Research on Cancer  
R: Risk  
S: Safety  
LC50: Lethal Concentration 50%  
LD50: Lethal Dose 50%  
BOD: Biological Oxygen Demand  
KoC: Soil Organic Carbon Partition Coefficient

**For further information email:** [msdstechnical@berryplastics.com](mailto:msdstechnical@berryplastics.com)

**Prepared By:** EnviroNet LLC.

The information and recommendations presented in this MSDS are based on sources believed to be accurate. Berry Plastics Corporation, Tapes and Coatings Division assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the **material** for their particular purposes. In particular, we make NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use **or disposal** of the material is in accordance with applicable Federal, State, and local laws and regulations.

---