

# AIRSEAL® ZERO

## HIGH PERFORMANCE DUCT SEALANT



### FEATURES

- 0 REPORTABLE VOC's
- LEED EQ Credit 4.1
- Cures to a tough, flexible film
- Excellent adhesion
- Formulated for Indoor / Outdoor use
- Exceeds all SMACNA Pressure and Sealing Classes.
- Dries to touch in minutes

### TECHNICAL SPECIFICATIONS

Packaging	(24) 10.5 oz. tubes, (12) 29 oz. tubes, or (4) 1 gal. pails
Shelf Life	18 months in unopened containers
Pressure Rating	Maximum 20" water column pressure
Coverage Rate	Approximately 80 SF per gal. 10.5 tube yields 32 LF @ 1/4" bead, 29 oz. tube yields 90 LF @ a 1/4" bead.
Solids Content	76% ± 1% by weight
Weight per gal.	9.8 lbs. ± 0.5 lbs.
Color	Red, Gray
Temperature Limits	Storage and application .....0°F to 115°F Service.....-40°F to 200°F
Class 1 Smoke and Flame Rating <b>LEED COMPLIANT</b> SCAQMD Rule 1168	SURFACE BURNING CHARACTERISTICS Flame Spread .....10 Smoke Developed .....5 Tested in accordance with UL 723, and ASTM E-84. Satisfies the requirements of NFPA 90A, 90B, and 225.

### RECOMMENDED USES

Use **AIRSEAL ZERO** to pressure seal all types of HVAC duct systems including metal and fiberglass ductboard.

### APPLICATION INSTRUCTIONS

Apply to clean, dry surfaces, free from oils, dirt and foreign matter. Spread at a minimum of 16 mils. wet film thickness with a brush or caulking gun. Seal all joints, seams and penetrations in the ductwork to ensure an airtight system. Dries to touch in minutes. Prior to pressure testing, allow 24 hours dry time depending on temperature, humidity and application thickness. Full cure is 72 hours. Can be applied in **moist** conditions.


### SAFETY PRECAUTIONS

CONSULT MANUFACTURERS MATERIAL SAFETY DATA SHEET. **EXTREMELY FLAMMABLE!** KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME. Vapors may ignite. Use only with adequate ventilation. Prolonged inhalation of vapors may be irritating. Avoid prolonged contact with skin. May be harmful if swallowed. **FIRST AID:** In case of skin contact, flush immediately with water for at least 15 minutes. For eye contact, call a physician immediately. If swallowed, do not eat, drink, or induce vomiting, call a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

### CLEAN UP

Use mineral spirits or similar solvent with appropriate safety precautions.

Polymer Adhesives Sealant Systems Inc., is proud to be affiliated with the following organizations:



**POLYMER ADHESIVES**

**SEALANT SYSTEMS, INC.**

[www.polymeradhesives.com](http://www.polymeradhesives.com)