



## Gobi II

The all new Gobi II condensate pump has been completely redesigned retaining all the good features you like and upgrading everything else. The Gobi II has a massive flow range allowing its use from 6,000 Btu/H (1.75kW) up to 120,000 Btu/H (35 kW). Its digital water sensor, universal voltage and user configurable flow ensure it is the strongest, quietest under A/C mounted condensate pump on the market today.

### Technical Data:

Maximum flow rate:	42 l/h (11 GPH)
Maximum suction:	3 m (10 ft.) self priming
Maximum head:	20.0 m(65.60 ft.)
Sound:	20dBA at 1 m (3 ft.)/19dBA at 1 m EN-ISO 3774:2010
Wireless access:	Remote wireless access with smartphone (optional feature)
Voltage:	100 ~ 240 VAC 50/60 Hz auto sensing universal power input
Power:	12 watts during maximum operation at 110V
Alarm relay:	10 Amps NO/NC contacts with integrated replacable 5 x 20 mm HRC 10A fuse
Weight:	600g (1.3 lbs.)
Discharge star tube:	6.0 mm I.D. (1/4") x 1 m (3.3 ft.)
Pump-sensor-tube:	Lenght 5 ft, dia. 3.3 mm (1/8")
Protection:	Class II double insulation, Fully potted, IP-44
Operation temp:	Ambient 3 °C to 40 °C (37.5 °F to 104 °F) / Water 5°C to 25°C (41°F to 77°F)
Compliance:	Conforms to UL: 778 and certified to CSA C22.2 #68



**Part No 3004045**