



The new degree of comfort.™

WATER HEATING

PR^oDUCT

GUIDE



INTEGRATED AIR & WATER

Rheem.com



INTEGRATED HEATING & WATER HEATING SYSTEM INSTALLATION

INTEGRATED HEATING & WATER HEATING

Home heating and water heating solutions, powered by tankless technology, provide integrated home comfort in one efficient system. When a call for heat is made, the tankless water heater acts as the heat-source for the air handler, providing both hot water and heating for the home.

TANKLESS GAS WATER HEATERS



PRESTIGE HIGH EFFICIENCY CONDENSING

- Indoor Direct Vent and Outdoor models
- Ultra Low NOx natural gas and LP models
- 9.5 gal./min. at 35° F rise
- 9.0 gal./min. at 35° F rise
- 8.4 gal./min. at 45° F rise
- 11,000 – 199,900 Btu/h max.

Limited Warranty

- Heat Exchanger – 12 Years
- Parts – 5 Years
- Labor – 1 Year



MID-EFFICIENCY TANKLESS

- Indoor Direct Vent and Outdoor models
- Ultra Low NOx natural gas and LP models
- 9.5 gal./min. at 35° F rise
- 7.4 gal./min. at 45° F rise
- 11,000 – 199,900 Btu/h max.

Limited Warranty

- Heat Exchanger – 12 Years
- Parts – 5 Years
- Labor – 1 Year

HYDRONIC AIR HANDLER



RHWB

- EcoTech™ or PSC motor available
- Hydronic coil
- Nominal heating capacities (with tankless models): 32,000 to 90,000 Btu/h

Limited Warranty

- Parts – 5 Years
- Labor – 1 Year

SOLPAK™ WATER HEATING SOLUTIONS

Solar water heating systems can provide up to 80% of a home's hot water. The efficiency, reliability, versatility and hot water delivery is unmatched. Homeowners can choose from a variety of systems ensuring they have the best solution for their needs.



SOLPAK™ ACTIVE SYSTEMS WITH ELECTRIC BACKUP

- HE tank, collectors and pump station
- 65, 80 and 120-Gallon capacities
- Collectors in three sizes: 3' x 8', 4' x 8' and 4' x 10'
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- Collectors OG-100 certified by SRCC
- System OG-300 certified by SRCC

Limited Warranty

- Tank – 6 Years
- Collector – 10 Years
- Pump Station – 6 Years



SOLPAK™ ACTIVE SYSTEMS WITH GAS BACKUP

- HE tank, collectors and pump station
- 75-Gallon capacity
- 3' x 8' and 4' x 8' collectors
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- Collectors are OG-100 certified by SRCC
- OG-300 certification by SRCC pending

Limited Warranty

- Tank – 6 Years
- Collector – 10 Years
- Pump Station – 6 Years

F^OCUS ON PERFORMANCE

To raise the bar in product performance, we've **set a new standard** in just about every area. Today, our high efficiency water and air solutions offer **lower energy consumption, easier installation** and **fewer maintenance needs**. As a result, many of our products are ENERGY STAR® qualified, contribute to LEED certification and provide some of the best warranties in the industry. With our focus on creating the type of high efficiency solutions that consumers demand, we're delivering **a new degree of comfort** for home and business environments across a range of products.

HIGH EFFICIENCY RESIDENTIAL WATER HEATERS

Rheem high efficiency gas and electric water heaters provide homeowners with not only the comfort of hot water, but substantial energy savings as well. Rheem offers the largest line of ENERGY STAR® qualified water heaters on the market. With our new hybrid, tankless, powered damper and induced draft models, homeowners are sure to find the perfect solution for their individual application needs.



PRESTIGE HYBRID HEAT PUMP WATER HEATER

- High 2.45 EF
- 8700 Btu/h compressor – the most powerful in its class
- Full-color LCD display
- 37-120° F Ambient operating temperature range
- EcoNet™ enabled
- 50-Gallon capacity
- 208-230 Volt, 1PH, 24 Amps

Limited Warranty
• Tank and Parts – 12 Years



PRESTIGE HIGH EFFICIENCY CONDENSING TANKLESS GAS

- Up to 94% efficient
- Indoor direct vent and outdoor models
- Vents with standard PVC – lower cost, readily available, and easy to install
- Built-in condensate neutralizer – reduces installation cost and time
- 11,000 – 199,900 Btu/h max.

Limited Warranty
• Heat Exchanger – 12 Years
• Parts – 5 Years



PRESTIGE HIGH EFFICIENCY CONDENSING POWER DIRECT VENT

- .82 EF for low operating costs
- Innovative technology
- Long vent runs up to 60 feet with plastic pipe
- Natural gas and LP
- FVIR compliant
- 38 and 48-Gallon capacities
- Up to 40,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC PLUS INDUCED DRAFT

- .70 EF
- Compact, high Btu/h
- Energy efficient/low emissions
- 29-Gallon capacity
- 60,000 Btu/h – 90-Gallon FHR performance

Limited Warranty
• Tank and Parts – 8 Years



PRESTIGE PLUS POWERED DAMPER

- .67 - .69 EF
- Energy efficient damper design
- Integrated self-diagnostic system control, flammable vapor detection sensor
- EcoNet™ enabled
- 38 and 50-Gallon capacities
- Up to 50,000 Btu/h

Limited Warranty
• Tank and Parts – 12 Years

ULTRA HIGH EFFICIENCY COMMERCIAL WATER HEATING

Ultra high efficiency Rheem commercial water heaters provide businesses up to 97% thermal efficiencies delivering substantial amounts of low-cost hot water required for commercial applications. They are also equipped with sophisticated diagnostic systems for ease of installation and maintenance.



SPIDERFIRE®

- Sealed-combustion design delivers 97% thermal efficiency dramatically reducing operating cost
- LCD control system
- 130,000 - 399,900 Btu/h
- 80 and 100-Gallon capacities

Limited Warranty
• Tank – 3 Years, upgradable to 5 Years



SUPER DUTY

- Advanced new line of condensing gas water heaters that delivers 93% thermal efficiency
- Patented heat transfer system to cut fuel costs and built to last
- Vents with 4" or 6" diameter PVC plastic pipe
- LCD interface
- 119 and 125-Gallon capacities
- 500,000 Btu/h

Limited Warranty
• Tank – 3 Years
• Parts – 1 Year



PRESTIGE HIGH EFFICIENCY CONDENSING POWER DIRECT VENT

- .82 EF
- Long vent runs up to 60 feet with plastic pipe
- Natural gas and LP
- 38 and 48-Gallon capacities
- Up to 40,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



PRESTIGE POWER DAMPER

- .67 - .69 EF
- Energy efficient damper design
- Integrated self-diagnostic system control, flammable vapor detection sensor
- EcoNet™ enabled
- 38 and 50-Gallon capacities
- Up to 50,000 Btu/h

Limited Warranty
• Tank and Parts – 12 Years



PRESTIGE POWERED DAMPER ULTRA LOW NOx

- .68 EF
- Energy efficient damper design
- Integrated self-diagnostic system control, flammable vapor detection sensor
- EcoNet™ enabled
- 40 and 50-Gallon capacities
- 36,000 Btu/h

Limited Warranty
• Tank and Parts – 12 Years



CLASSIC PLUS INDUCED DRAFT

- .70 EF
- Recovery rate: 61 GPH at 90° F rise
- 29 Gallon capacity with 90-Gallon FHR performance
- Small foot print, 17 3/4 inch diameter
- 60,000 Btu/h, nat. gas only

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC PLUS POWERED DAMPER

- .67 - .69 EF
- Recovery rate: 36.4 to 50.5 GPH at a 90° F rise
- Energy efficient 24 VAC flue damper
- Meets 40 ng/J NOx requirements
- EcoNet™ enabled
- 38, 40, and 50-Gallon capacities
- Up to 50,000 Btu/h

Limited Warranty
• Tank and Parts – 8 Years

Residential Tank-Type Gas Continued



CLASSIC DIRECT VENT FOR MANUFACTURED HOUSING

- .62 - .63 EF
- Recovery rate: 30.3 GPH at a 90° F rise
- CSA and HUD certified
- Combustion air comes from outside
- 30 and 40-Gallon capacities
- Up to 30,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC DIRECT VENT CO-AXIAL FOR MANUFACTURED HOUSING

- .60 - .62 EF
- Recovery rate: 30.3 to 36.4 GPH at a 90° F rise, based on model
- CSA and HUD certified
- 40 and 50-Gallon capacities
- Up to 36,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years

TANKLESS GAS



PRESTIGE HIGH EFFICIENCY CONDENSING

- .92 - .94 EF
- For 2-3 bathroom homes
- Indoor direct vent and outdoor models
- Vents with standard PVC
- SCAQMD 1146.2 compliant
- 11,000 - 199,900 Btu/h max.
- Temperature upgrade kits with temperature range of 85° F to 185° F available for commercial and hydronic applications

Limited Warranty
• Heat Exchanger – 12 Years Residential; 5 Years Commercial
• Parts – 5 Years
• Labor – 1 Year



MID-EFFICIENCY

- .82 EF
- For 2-3 bathroom homes
- Indoor direct vent and outdoor models
- SCAQMD 1146.2 compliant
- 11,000 - 199,900 Btu/h max.
- Temperature upgrade kits with temperature range of 85° F to 185° F available for commercial and hydronic applications

Limited Warranty
• Heat Exchanger – 12 Years Residential; 5 Years Commercial
• Parts – 5 Years
• Labor – 1 Year

SOLAR



SOLPAK™ ACTIVE SYSTEM WITH ELECTRIC BACKUP

- HE Storage tank, collectors and pump station
- Collectors OG-100 certified by SRCC
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- System OG-300 certified by SRCC
- 65, 80 and 120-Gallon capacities; collectors available in 3 sizes

Limited Warranty
• Tank – 6 Years
• Collector – 10 Years
• Pump Station – 6 Years



SOLPAK™ ACTIVE SYSTEM WITH GAS BACKUP

- HE Storage tank, collectors and pump station
- Collectors OG-100 SRCC certified
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- System OG-300 certification by SRCC pending
- 75-Gallon capacity; collectors available in two sizes

Limited Warranty
• Tank – 6 Years
• Collector – 10 Years
• Pump Station – 6 Years



SOLPAK™ PUMP MASTER

- Complete package for closed loop glycol systems
- Includes cast iron 3 speed pump, differential controller and flow meter
- Compact insulated enclosure
- Pressure relief valve with pressure gauge and expansion tank connection

Limited Warranty
• 6 Years



SOLAR COLLECTORS

- OG-100 certified by SRCC
- Durable low iron tempered glass
- Integral mounting channel for easy installation
- Stainless steel fasteners
- Suitable for open and closed loop systems
- Copper absorber plate
- Can be mounted horizontally or vertically

Limited Warranty
• Collector – 10 Years



MARATHON® THERMAL STORAGE TANKS

- Specifically designed for alternative energy applications
- Large water connections for lower pressure drop
- Tank – impervious to rust, corrosion
- 50, 85 and 105-Gallon capacities, 2 port and 3 port configurations
- 240 Volt/Single Phase

Limited Warranty
• Tank – Lifetime
• Parts – 6 Years

Commercial Gas Continued



POWER VENT

- 80% Thermal efficiency
- Use where medium quantities of hot water are required
- Uses 3" or 4" schedule 40 PVC, CPVC or ABS pipe
- Vents up to 95 feet
- 75-Gallon capacity
- 75,100 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



POWER DIRECT VENT

- 80% Thermal efficiency
- Use where medium quantities of hot water are required
- Two pipe system: one pipe pulls in outside air for combustion; the other exhausts combustion gases
- Flammable vapor detection sensor
- 50 and 75-Gallon capacities
- 47,000 - 75,100 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



POWER VENT KITS

- Use with natural gas or LP Universal models
- Use for vent lengths up to a maximum of 50 feet including the vent terminal
- Vent terminal can be installed through combustible or non-combustible surfaces – heat shield is provided
- Inputs: 98,000 - 400,000 Btu/h

COMMERCIAL ELECTRIC



LARGE VOLUME HIGH-POWER

- Vertical round, square and horizontal
- Glass lined tank
- 150 to 2,500-Gallon storage
- 208, 240, 277, 380, 415 and 600 voltages
- 12 kW - 900 kW

Limited Warranty
• Tank – 3 Years
• Parts – 1 Year



HEAVY DUTY

- Surface mounted and immersion thermostat models available
- System Sentinel™ LED diagnostics
- 50, 85, 120 and 175-Gallon capacities
- 208, 240, 277 and 480 voltages
- 6 kW - 108 kW

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year
• Element – 3 Years



CLASSIC PLUS ATMOSPHERIC

- .59 - .62 EF
- Recovery rate: 36.4 to 61 GPH at a 90° F rise
- Meets 40 ng/J NOx requirements
- 40, 48, 50 and 55-Gallon capacities
- Up to 60,000 Btu/h

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC PLUS HEAVY DUTY ATMOSPHERIC

- Recovery capacity: 72.8 GPH at a 100° F rise
- Meets 40 ng/J NOx requirements
- 75 and 98-Gallon capacities
- 75,100 Btu/h

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC PLUS POWER DIRECT VENT

- .62 EF
- Recovery rate: 47.5 to 65.7 GPH at a 90° F rise
- Long venting options up to 100 ft.
- Meets 40 ng/J NOx requirements
- 50-Gallon capacity
- Up to 65,000 Btu/h

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC PLUS HEAVY DUTY POWER DIRECT VENT

- Recovery capacity: 72.8 GPH at a 100° F rise
- Long venting options up to 100 ft.
- Meets 40 ng/J NOx requirements
- 75-Gallon capacity
- 75,100 Btu/h

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC PLUS HEAVY DUTY POWER VENT

- Recovery capacity: 72.8 GPH at a 100° F rise
- Long venting options up to 100 feet
- Integrated self-diagnostic system
- 75-Gallon capacity
- 75,100 Btu/h

Limited Warranty
• Tank and Parts – 8 Years

RESIDENTIAL TANK-TYPE ELECTRIC | Professional Prestige™, Classic Plus™ & Classic™ Models



PRESTIGE HYBRID HEAT PUMP

- High 2.45 EF
- 8700 Btu/h compressor
- Full-color LCD display
- 37-120° F Ambient operating temperature range
- EcoNet™ enabled
- 50-Gallon capacity
- 208-230 Volt, 1PH, 24 Amps

Limited Warranty
• Tank and Parts – 12 Years



PRESTIGE

- .95 EF
- Recovery rate: 25 GPH at a 90° F rise
- Restored stainless steel dual heating elements
- Super Sentinel™ LED diagnostic system
- EcoNet™ enabled
- 40 and 50-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty
• Tank and Parts – 12 Years



CLASSIC PLUS

- .95 EF
- Recovery rate: 21 GPH at a 90° F rise
- Restored stainless steel dual heating elements
- System Sentinel™ LED diagnostic system
- 30, 40, 50 and 55-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty
• Tank and Parts – 8 Years



CLASSIC

- .95 EF
- Recovery rate: 21 GPH at a 90° F rise
- Restored stainless steel lower heating element
- 19.9 to 55-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC POINT-OF-USE

- Space-saving design for installation in limited spaces
- Single restored stainless steel heating element
- Automatic thermostat and over-temperature protector
- 2.5, 6, 10, 15, 20 and 30-Gallon capacities

Limited Warranty
• Tank and Parts – 6 Years



SOLARAIDE™ HE

- Designed for use with closed loop solar systems
- Choice of two models – storage tank or single element water heater
- A special 1/2" NPT opening is provided for installation for a "probe-type" thermistor
- Double wall, wrap around heat exchanger
- 80 and 120-Gallon capacity

Limited Warranty
• Tank and Parts – 6 Years



SOLARAIDE™ HE WITH GAS ASSIST

- For use in residential closed loop solar water heating applications
- Single tank solution
- Double wall, high efficient solar heat exchanger
- Fast recovery for high demand applications
- Front solar connections for easy installations
- 75-Gallon capacity
- 75,100 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



SOLARAIDE™ STORAGE

- Choice of a high efficiency 4500 Watt backup electric water heater or a storage tank
- Multi-port connections - top and sides
- 80 and 120 Gallon capacities

Limited Warranty
• Tank and Parts – 6 Years



SPIDERFIRE®

- Sealed-combustion design delivers up to 97% thermal efficiency reducing operating cost
- Faster, less costly venting – vent with standard 2", -3", -4" or -6" diameter PVC plastic pipe
- LCD control system
- 80 and 100-Gallon capacities
- 130,000 - 399,900 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



SUPER DUTY

- Advanced new line of condensing gas water heaters that delivers 93% thermal efficiency
- Patented heat transfer system to cut fuel costs and built to last
- Vents with 4" or 6" diameter PVC plastic pipe
- LCD interface
- 119 and 125-Gallon capacities
- 500,000 Btu/h

Limited Warranty
• Tank – 3 Years
• Parts – 1 Year



POWERPACK™

- System Sentinel™ LED diagnostics
- Minimal heat loss design
- Immersion thermostat
- Lifeguard™ stainless steel element
- ASME only
- 13, 19.9, 30 and 40-Gallon
- 208, 240, 277 and 480 voltages
- 3 kW - 36 kW capacities

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year
• Element – 3 Years



ECLIPSE™

- 98% Thermal efficiency
- Polybutene tank – durable and lightweight
- No anode rod required
- 85 and 105-Gallon capacities
- 208, 240, 277 and 480 voltages, single or three phase
- Inputs from 12, 18 and 24 kW

Limited Warranty
• Tank – 10 Years
• Parts – 1 Year



BOOSTER

- Designed to fit under counters and deliver sanitizing rinse for commercial dishwashers
- System Sentinel™ LED diagnostics
- Immersion thermostat
- Manual reset high limit control
- 6" stainless steel legs
- 208, 240, 277 and 480 voltages
- 6 kW - 54 kW

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



LIGHT DUTY

- Designed for any application needing moderate amounts of hot water
- Porcelain enamel lined tank
- Heavy duty anode rod
- 30, 38, 40, 47, 65, 80 and 120-Gallon capacities
- 208, 240, 277 and 480 voltages
- 3 kW - 12 kW

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



POINT-OF-USE

- Designed to eliminate costly temperature loss in long piping runs
- Porcelain enamel lined tank
- Heavy duty anode rod
- 2.5, 6, 10, 15, 20 and 30-Gallon capacities
- 120, 208, 240, 277 and 480 volts
- 1440 - 6000 watts

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



CLASSIC PLUS POWERED DAMPER ULTRA LOW NOx

- .68 EF
- Recovery rate: 36.4 GPH at a 90° F rise
- Energy efficient 24 VAC flue damper
- Meets 10 ng/J NOx requirements
- EcoNet™ enabled
- 40 and 50-Gallon capacities
- Ultra low NOx 36,000 Btu/h burner

Limited Warranty

- Tank and Parts – 8 Years



CLASSIC PLUS ULTRA LOW NOx

- .56 - .62 EF
- Recovery rate: 30.3 to 45.5 GPH at a 90° F rise, based on model
- Features the Guardian System
- Meets 10 ng/J NOx requirements
- 28, 38, 50 and 55-Gallon capacities
- 45,000 Btu/h

Limited Warranty

- Tank and Parts – 8 Years



CLASSIC PLUS HEAVY DUTY ULTRA LOW NOx

- Recovery capacity: 72.8 GPH at a 100° F rise
- Meets 14 ng/J NOx requirements
- Features flammable detection system
- 75 and 98-Gallon capacities
- 75,100 Btu/h, natural gas only

Limited Warranty

- Tank and Parts – 8 Years



CLASSIC ATMOSPHERIC

- .60 - .63 EF
- Recovery rate: 30.3 to 40.4 GPH at a 90° F rise, based on model
- Features the Guardian System
- Meets 40 ng/J NOx requirements
- 29, 30, 40 and 50-Gallon capacities
- Up to 40,000 Btu/h

Limited Warranty

- Tank and Parts – 6 Years



CLASSIC POWER VENT

- .67 EF
- Recovery rate: 32.4 to 42.4 GPH at a 90° F rise, based on model
- Long venting options up to 100 feet
- Whisper quiet blower
- 40 and 50-Gallon capacities
- Up to 42,000 Btu/h

Limited Warranty

- Tank and Parts – 6 Years



CLASSIC FOR MANUFACTURED HOUSING

- .95 EF
- Recovery rate: 17 to 21 GPH at a 90° F rise
- CSA and HUD certified
- Restored stainless steel upper heating element
- 20, 30, 40 and 50-Gallon capacities
- 240 volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years



TABLE TOP

- .88 EF
- Recovery rate: 21 GPH at a 90° F rise
- Designed for areas that require additional counter space
- Baked enamel counter top is acid and heat resistant
- 40-Gallon capacity
- 240 Volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years

TANKLESS ELECTRIC



TANKLESS ELECTRIC

- Easy to install
- Ideal for point-of-use applications
- Energy efficient, compact design – fits almost anywhere
- On-unit temperature control
- Six models available - 3.2 kW to 27 kW

Limited Warranty

- Heat Exchanger – 10 Years
- Parts – 1 Year

RESIDENTIAL PRODUCT FEATURES



GUARDIAN SYSTEM™

- One-of-a-kind air/fuel shut-off device offers double protection
- Maintenance free no filter to clean
- Standard replacement parts



EVERKLEEN™

- Self Cleaning device fights harmful sediment build-up with a high-velocity spiraling water stream - helps operating efficiency by saving energy, money and improving tank life



ADVANTAGEPLUS™

- Sealed-combustion design delivers 95% thermal efficiency
- Optimizes efficiency and operating reliability
- No chimney required
- 55, 80, and 119-Gallon capacities
- 100,000 - 199,900 Btu/h

Limited Warranty

- Tank – 3 Years
- Parts – 1 Year



UNIVERSAL™

- 80% Thermal efficiency
- Designed to fit into tight retrofit applications – compact with multiple water connections
- Space-saving tank design
- System Sentinel™ LED diagnostics
- Multi-flue tank design
- 35 to 100-Gallon capacities
- 98,000 - 399,900 Btu/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



UNIVERSAL™ LOW NOx

- 80% Thermal efficiency
- Designed to fit into retrofit applications
- System Sentinel™ LED diagnostics
- Low NOx burner meets 40 ng/J NOx requirements
- 35 to 100-Gallon capacities
- 125,000 - 399,900 Btu/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



UNIVERSAL™ ULTRA LOW NOx

- Up to 82% thermal efficiency
- Low NOx burner meets 14 ng/J NOx requirements
- Designed to fit in tight retrofit applications
- System sentinel LED diagnostics
- 35 to 100-Gallon capacities
- 125,000 to 399,900 Btu/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



UNIVERSAL™ INDUCED DRAFT

- 80% Thermal efficiency
- Universal tank design - multiple water connections
- Short floor to vent heights
- Small jacket diameters
- Multiple water connections
- 100-Gallon capacity
- 250,000 - 360,000 Btu/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year

STORAGE TANKS



STORAGE TANKS

- 80% Thermal efficiency
- Designed for applications that need large quantities of hot water in a short period of time
- Long tank life
- Fits through a 30"-33" opening
- 2" rigid foam insulation
- 80, 115 and 175-Gallon capacities

Limited Warranty

- Tank – 5 Years



LARGE VOLUME STORAGE TANKS

- 80% Thermal efficiency
- Porcelain enamel lined tank
- ASME certified
- Available in jacketed and non-jacketed models
- 200 to 950-Gallon capacities

Limited Warranty

- Tank – 5 Years



EcoNet™

Introducing EcoNet™, the smart home system for heating, cooling and water heating developed exclusively by Rheem.

The EcoNet™ WiFi Kits provide remote access to EcoNet™ Enabled Electric and Gas Water Heaters from mobile apps and a mobile friendly web portal.



Contractor Benefits:

EcoNet™ makes it easier than ever for homeowners to save energy and achieve that perfect temperature – all while giving you the diagnostics you need to deliver that perfect level of service.

- Equipment Detection – EcoNet™ automatically detects all connected equipment
- Equipment Alerts – Help homeowners identify what part of equipment requires attention before making service call
- Contact Info – Contractor contact details stored in the EcoNet™ app are automatically displayed when equipment alerts occur



CLASSIC POWER DIRECT VENT

- .67 EF
- Recovery rate: 38.4 to 40.4 GPH at a 90° F rise, based on model
- Long venting options up to 100 feet
- Whisper quiet blower
- 40 and 50-Gallon capacities
- Up to 40,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC DIRECT VENT

- .60 - .62 EF
- Recovery rate: 30.3 to 36.4 GPH at a 90° F rise
- Adjustable coaxial vent
- Longer venting options
- 40 and 50-Gallon capacities
- Up to 36,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC ULTRA LOW NOx

- .60 - .63 EF
- Recovery rate: 30.3 to 40.4 GPH at a 90° F rise, based on model
- Meets 10 ng/J NOx requirements
- Features the Guardian System
- 28, 38 and 48-Gallon capacities
- Up to 40,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC POWER VENT ULTRA LOW NOx

- .67 EF
- Recovery rate: 36.4 to 38.4 GPH at a 90° F rise, based on model
- Long venting options up to 100 feet
- Whisper quiet blower
- 40 and 50-Gallon capacities
- Up to 38,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years



CLASSIC ATMOSPHERIC FOR MANUFACTURED HOUSING

- .62 - .63 EF
- Recovery rate: 30.3 to 34.3 GPH at a 90° F rise, based on model
- CSA and HUD certified
- Features the Guardian System
- 29 and 40-Gallon capacities
- Up to 34,000 Btu/h

Limited Warranty
• Tank and Parts – 6 Years

WARRANTY OPTION



PROTECTIONPLUS™

- 6-Year models become 10, 8-Year models become 12-Year limited tank warranty
- Provides up to 135% additional anodic protection
- For use on all Rheem residential models except Manufactured Housing, Marathon, Point-of-Use, Hybrid Heat Pump, Table Top, Condensing Gas Models, Tankless or Thermal Expansion Tanks

THERM-X-GUARD



THERMAL EXPANSION TANKS

- Eliminates problems associated with the thermal expansion in closed loop systems
- Suitable for water heaters up to 120-gallon capacity and supply pressure up to 80 PSI
- Easy to install and maintenance free

Limited Warranty
• Tank and Parts – 5 Years

MARATHON®



MARATHON®

- .95 EF
- Recovery rate: 21 GPH at a 90° F rise
- Seamless, polybutene tank
- Light weight and easy to install
- 40 to 50-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty
• Tank – Lifetime
• Parts – 6 Years



MARATHON® POINT-OF-USE

- Ideal for condos, cabins and light-duty commercial applications
- Seamless, polybutene tank
- 15 and 20-Gallon capacities
- 120 and 240 Volt AC
- 2 kW and 3 kW elements

Limited Warranty
• Residential use:
• Tank – Lifetime, Parts – 6 Years
• Light duty commercial use:
• Tank – 10 Years, Parts – 6 Years



MARATHON® HEAVY DUTY

- Recovery capacity: 18.2 GPH at a 100° F rise
- Designed for harsh environments
- Lightweight and easy to install
- 75, 85 and 105-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty
• Tank – 10 Years
• Parts – 5 Years



XTREME™

- 80% Thermal efficiency
- Advanced line of fast recovery commercial water heaters – up to 756 GPH per hour at a 100° F rise
- Space-saving tank design
- 90-Gallon capacity
- High-input – 500,000 - 715,000 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



VENTMASTER™

- 80% Thermal efficiency
- Power direct vent – vents up to 50 feet
- Eliminates negative air pressure by drawing combustion air from outside
- Easy installation – 3" or 4" schedule 40 PVC pipe
- 100-Gallon capacity
- 150,000 and 250,000 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



HOT WATER SUPPLY HEATERS

- 82% Thermal efficiency
- Indoor and outdoor installations
- Certified for a 160 PSI maximum working pressure
- 136,000 - 1,826,000 Btu/h

Limited Warranty
• Tank – 1 Year
• Parts – 1 Year
• Heat Exchanger – 5-Years



MEDIUM-DUTY

- 80% Thermal efficiency
- Use where medium quantities of hot water are required
- Short floor-to-vent heights
- 48 to 100-Gallon capacities
- 54,000 - 80,000 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year



MEDIUM-DUTY ULTRA LOW NOx

- 80% Thermal efficiency
- Low NOx burner meets 14 ng/J NOx requirements
- Fits in tight retrofit applications; resists effects of negative air pressure
- Integrated system control
- 75 and 98-Gallon capacities
- 75,100 Btu/h

Limited Warranty
• Tank – 3 Years, upgradable to 5-years
• Parts – 1 Year

PARTS AND ACCESSORIES

Rheem offers a wide assortment of parts and accessories for all your water heating needs. For more information, see your Rheem Parts and Accessories Catalog, call **800.621.5622** or go to www.rheem.com/products/replacement_parts.

*ELITEXPRESS 48 HOUR DELIVERY

For more information, download feature sheet from Rheem.com or ask for form RR-160.

LIMITED WARRANTY

See Rheem Warranty Certificate for complete information.

 Additional state and local incentives may also be available. Please consult with your tax advisor for eligibility requirements and amount of tax credit.

[†]LEED points may apply for specific products. See product spec sheet for details.

^{**}Commercial tankless products are not ENERGY STAR® qualified when converted from a residential configuration.





The new degree of comfort.™


Contact Us

Water Heating Division334.260.1500
 Customer Service, Warranty, Parts800.621.5622
 Tankless Customer Service, Warranty, Parts.....866.720.2076
 Technical Service.....800.HEATER3
 (800.432.8373)
 Technical Service for Hybrid Water Heater.....800.995.0982
 Fax.....800.535.9538
 Sales.....sales@rheem.com
 Marketing Communicationsmarcomm@rheem.com
 Website..... Rheem.com

Why Rheem?

Rheem helps you give your customers the **value, performance** and **features** they want. From our tried and true tank-type water heaters to our space-saving tankless solutions that provide continuous hot water, Rheem has something to **satisfy the budgets** and **lifestyles** of every customer.

In addition to our large selection of **water heating solutions**, Rheem also has a full line of **heating** and **cooling** products for warm winter nights, cool summer days and hot water all year round.



In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating
101 Bell Road • Montgomery, AL 36117-4305



INTEGRATED AIR & WATER

Rheem.com

PRINTED IN U.S.A. 03/15 WP FORM NO. 101-95 Rev. 18