

## INDUSTRIAL GRADE COATED GAFFER'S TAPE

### TYPICAL APPLICATIONS

- For A/V, TV, photography, theatrical and motion picture industries to bundle wires, color-code, and tape down lighting and props
- Masking silk-screen frames
- Protection and book-binding

### ADVANTAGES AND BENEFITS

- Waterproof backing
- Excellent holding power
- Conformable
- Durable
- Excellent weathering features
- Very high tensile strength











### CONSTRUCTION

Overall Grade/Function: Industrial Grade

Backing: Lusterless, vinyl or acrylic coated cloth

Adhesive: Synthetic Rubber

### COLOR(S)

	Black (BLK)		Brown (BRN)		Green (GRN)		Yellow (YEL)		Olive (OLV)
	White (WHI)		Gray (GRY)		Red (RED)		Blue (BLU)		Burgundy (BRG)

### STANDARD WIDTH(S)

48 mm      72 mm

### STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	10.5 mils	0.26 mm
Elongation	5%	5%
Service Temperature Range	50° F to 200° F	10° C to 93° C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC Form# TDS-P-628-04/08/2013

