

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Sealing seams in scrim reinforced foil duct insulation
- > Use in all weather conditions and when a maximum strength tape is needed

ADVANTAGES AND BENEFITS

- > Wrinkle-free backing
- > Permanent bond adhesive
- > Backing resists tearing
- > Resists water vapor and smoke transmission
- > Solvent free

CONSTRUCTION

Overall Grade/Function: HVAC

Backing: Aluminum foil/fiberglass scrim/kraft paper

Adhesive: High tack, synthetic rubber adhesive

Liner: Non-contaminating, siliconized, flat, white, paper release liner (thickness below does not include liner)

COLOR(S)



Silver (SIL)

STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

46 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	43 lbs/in width	75.3 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness (with liner)	9.4 mils	0.24 mm
Thickness (without liner)	6.6 mils	0.16 mm
Elongation	1 %	1 %
Application Temperature Range	32 F to 230 F	0 C to 110 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 10/SDI10; US Green Building Council - LEED® Point contributor product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

