



SUPPLIED DETACHED:
1-INSTRUCTION FORM

SLEEVE BEARING MOTOR
USE WITH 10.0 MFD VAC CAPACITOR

4 LEADS, (2) YEL & (2) ORG
#18, .031 THICK INSUL. FOR
REV. ROTATION LEADS TO BE
PROTECTED WITH A 3 HOLE
GROMMET.

ROTATION: C.C.W. VIEWING LEAD END
WITH ORG TO ORG & YEL TO YEL .
TO REVERSE ROTATION INTERCHANGE
ORG & YEL LEADS.

NIDEC MOTOR CORPORATION 05-Nov-12

MODEL	REF	CUSTOMER	HP	VOLTS	AMPS	HZ	RPM	ROTATION	CUSTOMER PN
KA55HXSGG-8671		STANDARD	1/2	208-230	2.9	60	1075/2 SPD	CCW LEAD END REV	8671

SHEET NUMBER	REV	REVISION RECORD FOR: C6407-00
1 OF 1	C	UPDATED ENGINEER APPROVED TO B. GAITAN
REVISION DATE		
17-OCT-12		

INFORMATION DISCLOSED ON THIS DOCUMENT IS CONSIDERED PROPRIETARY AND SHALL NOT BE REPRODUCED OR DISCLOSED WITHOUT WRITTEN CONSENT OF NIDEC MOTOR CORPORATION

NIDEC MOTOR CORPORATION

ALL DIMENSIONS ARE FOR REFERENCE ONLY UNLESS TOLERANCE IS GIVEN

ISSUED BY	REVIEWED BY	ENGINEER APPROVED	TITLE	CODE	ITEM NO.	SIZE
R. MORALES	M. LARGENT	B. GAITAN	ASSEMBLED VIEW	V01	332999	A